

1200 SSD

Data Sheet

Ultra-Fast, Consistent Performance Plus 12Gb/s SAS

- Helps remove storage bottlenecks and close the gap between processor and data access performance
- Delivers the speed and performance consistency needed for demanding enterprise applications
- Designed to reduce data access wait times under the most complex, write-intensive workloads
- First SSD to ship in volume with 12Gb/s SAS while ensuring the highest level of reliability and scalability
- Ensures data availability for critical production systems by using redundant, failover I/O communication paths
- Helps improve ROI by leveraging existing SAS infrastructures
- Custom-designed controller leverages Seagate enterprise expertise and manufacturing excellence
- Helps safeguard data against unexpected power loss and protects data from undetected, unintentional corruption
- Helps ensure data integrity with multiple layers of I/O error detection and correction
- Strong data security with Self-Encrypting Drive (SED) and FIPS SED models^{1,2}

Best-Fit Applications

- Demanding, enterprise applications with complex, write-intensive and mixed workloads
- IOPS-hungry enterprise applications, such as high-performance computing, online transaction processing and heavy data analytics
- Enterprise applications that demand high data availability and integrity as well as interface failover redundancy
- External enterprise storage solutions (SAN, NAS, DAS) and servers



¹ Self-Encrypting Drives (SED) and FIPS 140-2 Validated drives are not available in all models or countries. May require TCG-compliant host or controller support.

² FIPS 140-2 in review. See FIPS 140-2 Level 2 Certificate at <http://csrc.nist.gov/groups/STM/cmvp/validation.html>

1200 SSD



Specifications	800GB ¹	400GB ¹	200GB ¹
SED Models	ST800FM0053 ²	ST400FM0073 ²	ST200FM0073 ²
FIPS 140-2 Models	ST800FM0063 ^{2,3}		
Interface Options	12Gb/s SAS	12Gb/s SAS	12Gb/s SAS
NAND Flash Type	MLC	MLC	MLC
Performance			
Sustained Data Transfer Rate, Max (MB/s)	800	800	800
I/O Data Transfer Rate, Max (MB/s)	1,200	1,200	1,200
I/Os per Second per Watt (IOPS/W)	17,647	19,672	19,672
Sequential Read/Write Command Rate (MB/s) Peak, 128KB	800/640	800/640	800/640
Random Read/Write Command Rate (IOPS) Peak, 4KB	120,000/40,000	120,000/40,000	120,000/40,000
Configuration/Reliability			
Nonrecoverable Read Errors per Bits Read, Max	1 per 10 ¹⁶	1 per 10 ¹⁶	1 per 10 ¹⁶
Annualized Failure Rate (AFR)	0.44%	0.44%	0.44%
Total Terabytes Written (TBW) over Warranty Period ⁴	14,600	7,300	3,650
Limited Usage-Based Warranty (years) ⁵	5	5	5
Power Management			
+12/+5V Max Start Current (A)	0.8/0.5	0.8/0.5	0.8/0.5
Average Sleep Power (W)	1.0	1.0	1.0
Average Idle Power (W)	3.2	2.5	2.5
Average Operating Power (W)	6.8	6.1	6.1
Environmental			
Internal Operating Temperature (°C)	0 to 60	0 to 60	0 to 60
Non-operating Temperature (°C)	-40 to 75	-40 to 75	-40 to 75
Temperature Change Rate/Hr, Max (°C)	20	20	20
Relative Humidity, Noncondensing (%)	5 to 95	5 to 95	5 to 95
Shock, 0.5ms (Gs)	1,000	1,000	1,000
Vibration, 20Hz to 2,000Hz (Grms)	11.08	11.08	11.08
Physical			
Height (mm/in) ⁶	7.0/0.276	7.0/0.276	7.0/0.276
Width (mm/in) ⁶	70.10/2.76	70.10/2.76	70.10/2.76
Depth (mm/in) ⁶	100.45/3.955	100.45/3.955	100.45/3.955
Weight (g/lb)	100/0.220	100/0.220	100/0.220
Carton Unit Quantity	20	20	20
Cartons per Pallet	45	45	45
Cartons per Layer	9	9	9

¹ One gigabyte, or GB, equals one billion bytes when referring to drive capacity.

² Self-Encrypting Drives (SED) and FIPS 140-2 Validated drives are not available in all models or countries; may require TCG-compliant host or controller support.

³ FIPS 140-2 in review. See FIPS 140-2 Level 2 Certificate at <http://csrc.nist.gov/groups/STM/cmvp/validation.html>

⁴ Per the JEDEC JESD218A standard, using enterprise workload JESD219A with all LBAs allocated

⁵ Warranty period is either 5 years or when the device reaches the Total TBW Over warranty period, whichever comes first.

⁶ The drive physical dimensions conform to the Small Form Factor Standard (SFF-8201) found at www.sffcommittee.org. For connector-related dimensions, see SFF-8223.

www.seagate.com

AMERICAS Seagate Technology LLC 10200 South De Anza Boulevard, Cupertino, California 95014, United States, +1 408 658 1000
 ASIA/PACIFIC Seagate Singapore International Headquarters Pte. Ltd. 7000 Ang Mo Kio Avenue 5, Singapore 569877, +65 6485 3888
 EUROPE, MIDDLE EAST AND AFRICA Seagate Technology SAS 16-18 rue du Dôme, 92100 Boulogne-Billancourt, France, +33 1 41 86 10 00

© 2013 Seagate Technology LLC. All rights reserved. Printed in USA. Seagate, Seagate Technology and the Wave logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. The FIPS logo is a certification mark of NIST, which does not imply product endorsement by NIST, the U.S., or Canadian governments. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Actual data rates may vary depending on operating environment and other factors. The export or re-export of hardware or software containing encryption may be regulated by the U.S. Department of Commerce, Bureau of Industry and Security (for more information, visit www.bis.doc.gov), and controlled for import and use outside of the U.S. Seagate reserves the right to change, without notice, product offerings or specifications. DS1781.2-1304GB, April 2013