

Data Sheet

# Pipeline HD<sup>®</sup>

Cool - Quiet - Low Power

## Key Advantages

- Optimised one-disc, 1TB performance — perfect for high-definition consumer DVR applications
- Low power, quiet hard drives fine tuned for consistent, dependable delivery of multiple high-definition video streams with capacities from 250GB to 2TB
- Designed to meet Energy Star and other strict consumer power consumption standards
- Quiet drive operation to enhance customer viewing and listening experiences
- Easy-to-manage multi-room video delivery of at least ten simultaneous HD streams
- Qualified for operating temperatures up to 75°C to meet the rigours of the consumer electronics set-top box market
- 24x7 operational profile to meet the always-on demands of the DVR market

## Best-fit Applications

- Consumer digital video recorders
- Media servers and centres
- Home cinema PCs and servers
- Cable, satellite and IPTV set-top boxes



# Pipeline HD<sup>®</sup>

Cool - Quiet - Low Power



Specifications	2TB <sup>1</sup>	1.5TB <sup>1</sup>	1TB <sup>1</sup>	500GB <sup>1</sup>	320GB <sup>1</sup>	250GB <sup>1</sup>
Model Number	ST2000VM002	ST1500VM002	ST1000VM002	ST3500312CS	ST3320311CS	ST3250312CS
Interface	SATA 3Gb/s NCQ	SATA 3Gb/s NCQ	SATA 6Gb/s NCQ	SATA 3Gb/s NCQ	SATA 3Gb/s NCQ	SATA 3Gb/s NCQ
<b>Performance</b>						
Cache, Multi-segmented (MB)	64	64	64	8	8	8
SATA Transfer Rates Supported (Gb/s)	3.0/1.5	3.0/1.5	6.0/3.0/1.5	3.0/1.5	3.0/1.5	3.0/1.5
Simultaneous SDTV Streams Supported (Assumes 256K host buffer per stream)	10	10	20	10	10	10
Simultaneous HDTV Streams Supported (Assumes 2MB host buffer per stream)	10	10	16	10	10	10
Power-on to Ready (typical, sec)	<15	<15	<6	<12	<12	<12
Standby to Ready (typical, sec)	<15	<15	<6	<12	<12	<12
Maximum External Transfer Rate (MB/s)	300	300	600	300	300	300
<b>Voltage</b>						
Voltage Tolerance (including noise)	5V ± 5% 12V ± 10%	5V ± 5% 12V ± 10%	5V ± 5% 12V ± 10%	5V ± 5% 12V ± 10%	5V ± 5% 12V ± 10%	5V ± 5% 12V ± 10%
<b>Environmental</b>						
Halogen-free	Yes	Yes	Yes	Yes	Yes	Yes
Ambient Temperature (°C)						
Operating (ambient min)	0	0	0	0	0	0
Operating (drive case max)	75	75	75	75	75	75
Non-operating (ambient min)	-40	-40	-40	-40	-40	-40
Non-operating (ambient max)	70	70	70	70	70	70
Temperature Gradient, Operating/Non-operating (°C per hour max)	20/30	20/30	20/30	20/30	20/30	20/30
Relative Humidity, Operating/Non-operating (non-condensing, %)	5 to 95/5 to 95	5 to 95/5 to 95	5 to 95/5 to 95	5 to 95/5 to 95	5 to 95/5 to 95	5 to 95/5 to 95
Wet Bulb Temperature, Operating/Non-operating (°C)	37.7/40.0	37.7/40.0	37.7/40.0	37.7/40.0	37.7/40.0	37.7/40.0
<b>Shock</b>						
Operating: 2ms (max, Gs)	80	80	80	70	70	70
Non-operating: 2ms (max, Gs)	300	300	350	350	350	350
<b>Vibration, Operating</b>						
5Hz to 22Hz (limited displacement) (Gs)	0.25	0.25	0.25	0.50	0.50	0.50
22Hz to 350Hz (Gs)	0.50	0.50	0.50	0.50	0.50	0.50
350Hz to 500Hz (Gs)	0.25	0.25	0.25	0.25	0.25	0.25
<b>Vibration, Non-operating</b>						
5Hz to 350Hz (Gs)	3.0	3.0	3.0	5.0	5.0	5.0
350Hz to 500Hz (Gs)	3.0	3.0	3.0	1.0	1.0	1.0
<b>Power Management</b>						
Start-up Current (12V typical, A)	2.0	2.0	2.0	2.0	2.0	2.0
Consumer Storage Profile (W)	4.93	4.93	3.7	3.4	3.4	3.4
Idling, Average (W)	4.5	4.5	2.5	3.0	3.0	3.0
Standby/Sleep Mode (typical, W)	0.5	0.5	0.8	0.7	0.6	0.7
<b>Acoustics</b>						
PVR Profile (typical/max, bels)	2.0/2.2	2.0/2.2	1.9/2.1	1.9/2.0	1.9/2.0	1.9/2.0
<b>Reliability</b>						
Contact Start-Stop Cycles (25°C, 50% relative humidity)	—	—	—	50,000	50,000	50,000
Load/Unload Cycles (25°C, 50% relative humidity)	300,000	300,000	300,000	—	—	—
Non-recoverable Read Errors per Bits Read	1 sector per 10 <sup>15</sup>	1 sector per 10 <sup>15</sup>	1 sector per 10 <sup>15</sup>	1 sector per 10 <sup>15</sup>	1 sector per 10 <sup>15</sup>	1 sector per 10 <sup>15</sup>
Annualised Failure Rate (AFR)	0.55%	0.55%	0.55%	0.55%	0.55%	0.55%
Power-on Hours	8,760	8,760	8,760	8,760	8,760	8,760
<b>Dimensions</b>						
Height (mm/in)	26.10/1.028	26.10/1.028	20.20/0.795	20.20/0.795	20.20/0.795	20.20/0.795
Width (mm/in)	101.60/4.0	101.60/4.0	101.60/4.0	101.85/4.010	101.85/4.010	101.85/4.010
Depth (mm/in)	147.0/5.78	147.0/5.78	147.0/5.78	146.99/5.787	146.99/5.787	146.99/5.787
Weight (g/lb)	635/1.39	635/1.39	415/0.915	415/0.915	415/0.915	415/0.915
Carton Unit Quantity	20	20	25	25	25	25
Cartons per Pallet	40	40	40	40	40	40
Cartons per Layer	8	8	8	8	8	8

<sup>1</sup> One gigabyte, or GB, equals one billion bytes; and one terabyte, or TB, equals one trillion bytes when referring to drive capacity.

[www.seagate.com](http://www.seagate.com)



AMERICAS Seagate Technology LLC 10200 South De Anza Boulevard, Cupertino, California 95014, United States, +1 408 658 1000  
 ASIA/PACIFIC Seagate Singapore International Headquarters Pte. Ltd. 7000 Ang Mo Kio Avenue 5, Singapore 569877, +65 6485 3888  
 EUROPE, MIDDLE EAST AND AFRICA Seagate Technology SAS 16-18 rue du Dôme, 92100 Boulogne-Billancourt, France, +33 1 41 86 10 00

© 2012 Seagate Technology LLC. All rights reserved. Printed in USA. Seagate, Seagate Technology and the Wave logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. Pipeline, Pipeline HD and the Think Green Logo are either trademarks or registered trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes; and one terabyte, or TB, equals one trillion bytes. Your computer operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Actual data rates may vary depending on operating environment and other factors. Seagate reserves the right to change, without notice, product offerings or specifications. DS1693.5-1201GB, January 2012