

# Desktop HDD

Data Sheet

## The Power of One

- Seagate brings over 30 years of trusted performance and reliability to the new Seagate® Desktop HDDs—now available in capacities up to 6TB
- Increase your capacity and drive down costs with up to 1TB-per-disk hard drive technology
- SATA 6Gb/s interface optimises burst performance.
- Seagate AcuTrac™ servo technology delivers dependable performance
- Free DiscWizard™ software enables high capacities on legacy PC BIOS systems
- Seagate Secure™ models provide hardware-based data security and deliver an Instant Secure Erase feature for safe, fast and easy drive retirement<sup>1</sup>
- Seagate Secure models meet the NIST 800-88 media sanitization specification and also support the Trusted Computer Group (TCG) Opal standard<sup>1</sup>

## Best-fit Applications

- Desktop or all-in-one PCs
- Home servers
- Entry-level direct-attached storage devices (DAS)



<sup>1</sup> Seagate Secure models are not available in all countries. May require TCG-compliant host or controller support.



# Desktop HDD



| Specifications                                 | 6TB         | 5TB         | 4TB         | 3TB                | 2TB                |
|--|-------------|-------------|-------------|--------------------|--------------------|
| Standard Model Numbers <sup>1</sup>            | ST6000DM001 | ST5000DM002 | ST4000DM000 | ST3000DM001        | ST2000DM001        |
| Seagate Secure™ Model Numbers                  | —           | —           | —           | ST3000DM002        | ST2000DM002        |
| Model Name                                     | Desktop HDD | Desktop HDD | Desktop HDD | formerly Barracuda | formerly Barracuda |
| Interface                                      | SATA 6Gb/s  | SATA 6Gb/s  | SATA 6Gb/s  | SATA 6Gb/s         | SATA 6Gb/s         |
| <b>Performance</b>                             |             |             |             |                    |                    |
| Cache  | 128MB       | 128MB       | 64MB        | 64MB               | 64MB               |
| SATA Transfer Rates Supported (Gb/s)           | 6.0/3.0/1.5 | 6.0/3.0/1.5 | 6.0/3.0/1.5 | 6.0/3.0/1.5        | 6.0/3.0/1.5        |
| Average Data Rate, Read/Write                  | 180         | 180         | 146         | 156                | 156                |
| Max Sustainable Transfer Rate                  | 220MB/s     | 220MB/s     | 180MB/s     | 210MB/s            | 210MB/s            |
| <b>Configuration/Organisation</b>              |             |             |             |                    |                    |
| Heads/Discs                                    | 6/12        | 6/12        | 8/4         | 6/3                | 4/2                |
| Bytes per Sector                               | 512E        | 512E        | 512E        | 512E               | 512E               |
| <b>Voltage</b>                                 |             |             |             |                    |                    |
| Voltage Tolerance, Inc. Noise (5V)             | ±5%         | ±5%         | ±5%         | ±5%                | ±5%                |
| Voltage Tolerance, Inc. Noise (12V)            | ±10%        | ±10%        | ±10%        | ±10%               | ±10%               |
| <b>Reliability/Data Integrity</b>              |             |             |             |                    |                    |
| Contact Start/Stop Cycles                      | —           | —           | —           | —                  | —                  |
| Load/Unload Cycles                             | 300,000     | 300,000     | 300,000     | 300,000            | 300,000            |
| Non-recoverable Read Errors per Bits Read, Max | 1 per 10E14 | 1 per 10E14 | 1 per 10E14 | 1 per 10E14        | 1 per 10E14        |
| Workload Rate Limit (TB/year)                  | 55          | 55          | 55          | 55                 | 55                 |
| Power-on Hours                                 | 2400        | 2400        | 2400        | 2400               | 2400               |
| Warranty, Limited (years) <sup>2</sup>         | 2           | 2           | 2           | 2                  | 2                  |
| <b>Power Management</b>                        |             |             |             |                    |                    |
| Startup Power (12V, A)                         | 2.0         | 2.0         | 2.0         | 2.5                | 2.5                |
| Average Operating Power                        | 9.0W        | 9.0W        | 5.60W       | 8.0W               | 8.0W               |
| Idling Average                                 | 7.2W        | 7.2W        | 4.0W        | 5.40W              | 5.40W              |
| Standby Mode                                   | 0.6W        | 0.6W        | 0.5W        | 0.75W              | 0.75W              |
| Sleep Mode                                     | 0.6W        | 0.6W        | 0.5W        | 0.75W              | 0.75W              |
| <b>Environmental/Temperature</b>               |             |             |             |                    |                    |
| Operating (ambient, min)                       | 0°C         | 0°C         | 0°C         | 0°C                | 0°C                |
| Operating (drive case, max)                    | 60°C        | 60°C        | 60°C        | 60°C               | 60°C               |
| Non-operating (ambient, min)                   | -40°C       | -40°C       | -40°C       | -40°C              | -40°C              |
| Non-operating (ambient, max)                   | 70°C        | 70°C        | 70°C        | 70°C               | 70°C               |
| Halogen-free                                   | Yes         | Yes         | Yes         | Yes                | Yes                |
| RoHS compliance                                | Yes         | Yes         | Yes         | Yes                | Yes                |
| <b>Physical</b>                                |             |             |             |                    |                    |
| Height   | 26.11mm     | 26.11mm     | 26.11mm     | 26.11mm            | 26.11mm            |
| Height   | 1.028in     | 1.028in     | 1.028in     | 1.028in            | 1.028in            |
| Width  | 101.6mm     | 101.6mm     | 101.6mm     | 101.6mm            | 101.6mm            |
| Width  | 4.0in       | 4.0in       | 4.0in       | 4.0in              | 4.0in              |
| Depth  | 146.99mm    | 146.99mm    | 146.99mm    | 146.99mm           | 146.99mm           |
| Depth  | 5.787in     | 5.787in     | 5.787in     | 5.787in            | 5.787in            |
| Typical Weight                                 | 780g        | 780g        | 610g        | 626g               | 626g               |
| Typical Weight                                 | 1.72lb      | 1.72lb      | 1.35lb      | 1.38lb             | 1.38lb             |
| Carton Unit Quantity                           | 20          | 20          | 20          | 20                 | 20                 |
| Cartons per Pallet                             | 40          | 40          | 40          | 40                 | 40                 |
| Cartons per Layer                              | 8           | 8           | 8           | 8                  | 8                  |
| <b>Special Features</b>                        |             |             |             |                    |                    |
| Seagate AcuTrac™ Technology                    | Yes         | Yes         | Yes         | Yes                | Yes                |

| Specifications                                 | 1TB                | 500GB              | 320GB              | 250GB              |
|--|--------------------|--------------------|--------------------|--------------------|
| Standard Model Numbers <sup>1</sup>            | ST1000DM003        | ST500DM002         | ST320DM000         | ST250DM000         |
| Seagate Secure™ Model Numbers                  | ST1000DM004        | —                  | —                  | —                  |
| Model Name                                     | formerly Barracuda | formerly Barracuda | formerly Barracuda | formerly Barracuda |
| Interface                                      | SATA 6Gb/s         | SATA 6Gb/s         | SATA 6Gb/s         | SATA 6Gb/s         |
| <b>Performance</b>                             |                    |                    |                    |                    |
| Cache  | 64MB               | 16MB               | 16MB               | 16MB               |
| SATA Transfer Rates Supported (Gb/s)           | 6.0/3.0/1.5        | 6.0/3.0/1.5        | 6.0/3.0/1.5        | 6.0/3.0/1.5        |
| Average Data Rate, Read/Write                  | 156                | 125                | 125                | 125                |
| Max Sustainable Transfer Rate                  | 210MB/s            | 144MB/s            | 144MB/s            | 144MB/s            |
| <b>Configuration/Organisation</b>              |                    |                    |                    |                    |
| Heads/Discs                                    | 2/1                | 2/1                | 2/1                | 1/1                |
| Bytes per Sector                               | 512E               | 512E or 512        | 512E or 512        | 512E or 512        |
| <b>Voltage</b>                                 |                    |                    |                    |                    |
| Voltage Tolerance, Inc. Noise (5V)             | ±5%                | ±5%                | ±5%                | ±5%                |
| Voltage Tolerance, Inc. Noise (12V)            | ±10%               | ±10%               | ±10%               | ±10%               |
| <b>Reliability/Data Integrity</b>              |                    |                    |                    |                    |
| Contact Start/Stop Cycles                      | 50,000             | 50,000             | 50,000             | 50,000             |
| Load/Unload Cycles                             | 300,000            | —                  | —                  | —                  |
| Non-recoverable Read Errors per Bits Read, Max | 1 per 10E14        | 1 per 10E14        | 1 per 10E14        | 1 per 10E14        |
| Workload Rate Limit (TB/year)                  | 55                 | 55                 | 55                 | 55                 |
| Power-on Hours                                 | 2400               | 2400               | 2400               | 2400               |
| Warranty, Limited (years) <sup>2</sup>         | 2                  | 2                  | 2                  | 2                  |
| <b>Power Management</b>                        |                    |                    |                    |                    |
| Startup Power (12V, A)                         | 2.0                | 2.0                | 2.0                | 2.0                |
| Average Operating Power                        | 5.3W               | 5.3W               | 6.2W               | 6.19W              |
| Idling Average                                 | 4.60W              | 4.60W              | 4.60W              | 4.60W              |
| Standby Mode                                   | 0.94W              | 0.94W              | 0.79W              | 0.79W              |
| Sleep Mode                                     | 0.94W              | 0.94W              | 0.79W              | 0.79W              |
| <b>Environmental/Temperature</b>               |                    |                    |                    |                    |
| Operating (ambient, min)                       | 0°C                | 0°C                | 0°C                | 0°C                |
| Operating (drive case, max)                    | 60°C               | 60°C               | 60°C               | 60°C               |
| Non-operating (ambient, min)                   | -40°C              | -40°C              | -40°C              | -40°C              |
| Non-operating (ambient, max)                   | 70°C               | 70°C               | 70°C               | 70°C               |
| Halogen-free                                   | Yes                | Yes                | Yes                | Yes                |
| RoHS compliance                                | Yes                | Yes                | Yes                | Yes                |
| <b>Physical</b>                                |                    |                    |                    |                    |
| Height   | 19.99mm            | 19.99mm            | 19.99mm            | 19.99mm            |
| Height   | 0.787in            | 0.787in            | 0.787in            | 0.787in            |
| Width  | 101.6mm            | 101.6mm            | 101.6mm            | 101.6mm            |
| Width  | 4.0in              | 4.0in              | 4.0in              | 4.0in              |
| Depth  | 146.99mm           | 146.99mm           | 146.99mm           | 146.99mm           |
| Depth  | 5.787in            | 5.787in            | 5.787in            | 5.787in            |
| Typical Weight                                 | 400g               | 415g               | 415g               | 415g               |
| Typical Weight                                 | 0.88lb             | 0.92lb             | 0.92lb             | 0.915lb            |
| Carton Unit Quantity                           | 25                 | 25                 | 25                 | 25                 |
| Cartons per Pallet                             | 40                 | 40                 | 40                 | 40                 |
| Cartons per Layer                              | 8                  | 8                  | 8                  | 8                  |
| <b>Special Features</b>                        |                    |                    |                    |                    |
| Seagate AcuTrac™ Technology                    | No                 | No                 | No                 | No                 |

1 Seagate ships the 500GB, 320GB and 250GB models in both 4K- and 512-byte sectors. SmartAlign technology is included on 4K sector drives. Both drives are functionally and physically equivalent.

2 Extended warranty products available. Consult your distributor for details.

SEAGATE.COM

AMERICAS Seagate Technology LLC 10200 South De Anza Boulevard, Cupertino, California 95014, United States, 408-658-1000  
 ASIA/PACIFIC Seagate Singapore International Headquarters Pte. Ltd. 7000 Ang Mo Kio Avenue 5, Singapore 569877, 65-6485-3888  
 EUROPE, MIDDLE EAST AND AFRICA Seagate Technology SAS 16-18, rue du Dôme, 92100 Boulogne-Billancourt, France, 33 1-4186 10 00

LLC in the United States and/or other countries. AcuTrac, Barracuda, DiscWizard, Seagate Secure and SmartAlign are either trademarks or registered trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes; and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Actual data rates may vary depending on operating environment and other factors. The export or re-export of Seagate hardware or software is regulated by the U.S. Department of Commerce, Bureau of Industry and Security (for more information, visit [www.bis.doc.gov](http://www.bis.doc.gov)), and may be controlled for export, import and use in other countries. Seagate reserves the right to change, without notice, product offerings or specifications. DS1770.6-1507UK July 2015