

# Enterprise Capacity 3.5 HDD

Data Sheet

## Capacity-Optimised Enterprise Hard Drive for Bulk-Data Applications

- Highest-capacity large form factor enterprise drive - 50% more capacity over last generation with up to 6TB - for demanding data growth<sup>1</sup>
- Fastest high-capacity HDD with best-in-class random and sequential read/write performance
- Eighth-generation drive technology for reliable access to bulk storage of unstructured data
- Both 12Gb/s SAS and SATA 6Gb/s interfaces for easy integration into replicated and RAID storage systems
- Enhanced error correction, super parity and end-to-end SAS-based data integrity for accurate data storage
- Industry-leading rotational vibration tolerance ensures consistent performance
- Improved power and cooling efficiencies with low power consumption and on-demand PowerChoice™ technology based on T10/T13 power management standards
- Engineered for 24x7 workloads of 550TB/yr - 10x that of desktop drives
- Robust performance with dual processors, ramp load technology, top-cover-attached motor and humidity sensor for optimum performance in all chassis
- Self-Encrypting Drive (AES-256) with FIPS 140-2 validation and Seagate Instant Secure Erase cuts IT drive retirement costs while protecting data at rest securely<sup>2,3</sup>

## Best-fit Applications

- Hyperscale applications
- High-capacity RAID storage
- Mainstream enterprise external storage arrays (SAN, NAS, DAS)
- Cloud data centres - replicated bulk data storage
- Enterprise backup and restore - D2D, virtual tape
- Centralised surveillance



<sup>1</sup> Seagate recommends validating your configuration with your HBA/RAID controller manufacturer to ensure full capacity capabilities.

<sup>2</sup> Self-Encrypting Drives (SED) and FIPS 140-2 Validated drives are not available in all models or countries; may require TCG-compliant host or controller support.

<sup>3</sup> FIPS 140-2 in review. See FIPS 140- Level 2 Certificate at <http://csrc.nist.gov/groups/STM/cmvp/documents/140-1/1401val2011.htm#1635>

# Enterprise Capacity 3.5 HDD



Specifications	SATA 6Gb/s			
	6TB <sup>1,2</sup>	5TB <sup>1,2</sup>	4TB <sup>1,2</sup>	2TB <sup>1</sup>
Standard Model Number (4K Native)	ST6000NM0004	—	—	—
Standard Model Number (512 Emulation)	ST6000NM0024	ST5000NM0084	ST4000NM0024	ST2000NM0024
SED Model Number (512 Emulation)	ST6000NM0044 <sup>3</sup>	—	ST4000NM0044 <sup>3</sup>	ST2000NM0044 <sup>3</sup>
SED-FIPS Model Number (512 Emulation)	ST6000NM0084 <sup>3,4</sup>	—	—	—
<b>Features</b>				
Humidity Sensor	Yes	Yes	Yes	Yes
Super Parity	Yes	Yes	Yes	Yes
Low Halogen	Yes	Yes	Yes	Yes
PowerChoice™ Technology	Yes	Yes	Yes	Yes
Hot-Plug Support <sup>6</sup>	Yes	Yes	Yes	Yes
Cache, Multi-segmented (MB)	128	128	128	128
<b>Reliability/Data Integrity</b>				
Mean Time Between Failures (MTBF, hours)	1.4M	1.4M	1.4M	1.4M
Reliability Rating at Full 24x7 Operation (AFR)	0.63%	0.63%	0.63%	0.63%
Non-recoverable Read Errors per Bits Read	1 sector per 10 <sup>15</sup>	1 sector per 10 <sup>15</sup>	1 sector per 10 <sup>15</sup>	1 sector per 10 <sup>15</sup>
Power-On Hours per Year	8,760 (24x7)	8,760 (24x7)	8,760 (24x7)	8,760 (24x7)
Limited Warranty (years)	5	5	5	5
<b>Performance</b>				
Spindle Speed (RPM)	7,200	7,200	7,200	7,200
Interface Access Speed (Gb/s)	6.0, 3.0, 1.5	6.0, 3.0, 1.5	6.0, 3.0, 1.5	6.0, 3.0, 1.5
Max. Sustained Transfer Rate OD (MB/s)	216	216	216	216
Average Latency (ms)	4.16	4.16	4.16	4.16
Interface Ports	Single	Single	Single	Single
Rotational Vibration @ 1,500Hz(rad/s <sup>2</sup> )	12.5	12.5	12.5	12.5
<b>Power Consumption</b>				
Idle Power, Average (W)	6.9	6.9	6.0	4.5
Typical Operating, Random Read (W)	11.27	11.27	9.42	8.08
Power Supply Requirements	+12V and +5V	+12V and +5V	+12V and +5V	+12V and +5V
<b>Environmental</b>				
Temperature, Operating (°C)	5 to 60	5 to 60	5 to 60	5 to 60
Vibration, Non-operating: 10Hz to 500Hz (Grms)	5.0	5.0	5.0	5.0
Shock, Operating, 2ms (Read/Write) (Gs)	70/40	70/40	70/40	70/40
Shock, Non-operating, 1ms and 2ms (Gs)	250	300	300	300
<b>Physical</b>				
Height (in/mm, max) <sup>6</sup>	1.028/26.1	1.028/26.1	1.028/26.1	1.028/26.1
Width (in/mm, max) <sup>6</sup>	4.010/101.85	4.010/101.85	4.010/101.85	4.010/101.85
Depth (in/mm, max) <sup>6</sup>	5.878/147.0	5.878/147.0	5.878/147.0	5.878/147.0
Weight (lb/g)	1.720/780	1.720/780	1.400/635	1.344/605
Carton Unit Quantity	20	20	20	20
Cartons per Pallet	40	40	40	40
Cartons per Layer	8	8	8	8

<sup>1</sup> One gigabyte, or GB equals one billion bytes; and one terabyte or TB, equals one trillion bytes when referring to drive capacity.

<sup>2</sup> Seagate recommends validating your configuration with your HBA/RAID controller manufacturer to ensure full capacity capabilities.

<sup>3</sup> Self-Encrypting Drives (SED) and FIPS 140-2 Validated drives are not available in all models or countries; may require TCG-compliant host or controller support.

<sup>4</sup> FIPS 140-2 in review. See FIPS 140-2 Level 2 Certificate at: <http://csrc.nist.gov/groups/STM/cmpv/documents/140-1/1401val2011.htm#1635>

<sup>5</sup> These base deck dimensions conform to the Small Form Factor Standard (SFF-8201) found at [www.sffcommittee.org](http://www.sffcommittee.org). For connector-related dimensions, see SFF-8223.

<sup>6</sup> Supports Hotplug operation per Serial ATA Revision 2.6 specification.



# Enterprise Capacity 3.5 HDD



Specifications	12Gb/s SAS		
	6TB <sup>1,2</sup>	4TB <sup>1,2</sup>	2TB <sup>1</sup>
Standard Model Number (4K Native)	ST6000NM0014	—	—
Standard Model Number (512 Emulation)	ST6000NM0034	ST4000NM0034	ST2000NM0034
SED Model Number (512 Emulation)	ST6000NM0054 <sup>3</sup>	ST4000NM0054 <sup>3</sup>	ST2000NM0054 <sup>3</sup>
SED-FIPS Model Number (512 Emulation)	ST6000NM0104 <sup>3,4</sup>	—	—
<b>Features</b>			
Protection Information (T10 DIF)	Yes	Yes	Yes
Humidity Sensor	Yes	Yes	Yes
Super Parity	Yes	Yes	Yes
Low Halogen	Yes	Yes	Yes
PowerChoice Technology	Yes	Yes	Yes
Cache, Multi-segmented (MB)	128	128	128
<b>Reliability/Data Integrity</b>			
Mean Time Between Failures (MTBF, hours)	1.4M	1.4M	1.4M
Reliability Rating at Full 24x7 Operation (AFR)	0.63%	0.63%	0.63%
Non-recoverable Read Errors per Bits Read	1 sector per 10 <sup>15</sup>	1 sector per 10 <sup>15</sup>	1 sector per 10 <sup>15</sup>
Power-On Hours per Year	8,760 (24x7)	8,760 (24x7)	8,760 (24x7)
Limited Warranty (years)	5	5	5
<b>Performance</b>			
Spindle Speed (RPM)	7,200	7,200	7,200
Interface Access Speed (Gb/s)	12.0, 6.0, 3.0	12.0, 6.0, 3.0	12.0, 6.0, 3.0
Max. Sustained Transfer Rate OD (MB/s)	up to 226	up to 226	up to 226
Average Latency (ms)	4.16	4.16	4.16
Interface Ports	Dual	Dual	Dual
Rotational Vibration @ 1,500Hz(rad/s <sup>2</sup> )	12.5	12.5	12.5
<b>Power Consumption</b>			
Idle Power, Average (W)	7.97	5.73	4.84
Typical Operating, Random Read (W)	11.86	9.59	8.93
Power Supply Requirements	+12V and +5V	+12V and +5V	+12V and +5V
<b>Environmental</b>			
Temperature, Operating (°C)	5 to 60	5 to 60	5 to 60
Vibration, Non-operating: 10Hz to 500Hz (Grms)	4.9	4.9	4.9
Shock, Operating, 2ms (Read/Write) (Gs)	70/40	70/40	70/40
Shock, Non-operating, 1ms and 2ms (Gs)	250	300	300
<b>Physical</b>			
Height (in/mm, max) <sup>5</sup>	1.028/26.1	1.028/26.1	1.028/26.1
Width (in/mm, max) <sup>5</sup>	4.010/101.85	4.010/101.85	4.010/101.85
Depth (in/mm, max) <sup>5</sup>	5.878/147.0	5.878/147.0	5.878/147.0
Weight (lb/g)	1.720/780	1.400/635	1.344/605
Carton Unit Quantity	20	20	20
Cartons per Pallet	40	40	40
Cartons per Layer	8	8	8

<sup>1</sup> One gigabyte, or GB equals one billion bytes; and one terabyte or TB, equals one trillion bytes when referring to drive capacity.

<sup>2</sup> Seagate recommends validating your configuration with your HBA/RAID controller manufacturer to ensure full capacity capabilities.

<sup>3</sup> Self-Encrypting Drives (SED) and FIPS 140-2 Validated drives are not available in all models or countries; may require TCG-compliant host or controller support.

<sup>4</sup> FIPS 140-2 in review. See FIPS 140-2 Level 2 Certificate at: <http://csrc.nist.gov/groups/STM/cmvp/documents/140-1/1401val2011.htm#1635>

<sup>5</sup> These base deck dimensions conform to the Small Form Factor Standard (SFF-8201) found at [www.sffcommittee.org](http://www.sffcommittee.org). For connector-related dimensions, see SFF-8223.



[www.seagate.com](http://www.seagate.com)

AMERICAS Seagate Technology LLC 10200 South De Anza Boulevard, Cupertino, California 95014, United States, +1 408 658 1000  
 ASIA/PACIFIC Seagate Singapore International Headquarters Pte. Ltd. 7000 Ang Mo Kio Avenue 5, Singapore 569877, +65 6485 3888  
 EUROPE, MIDDLE EAST AND AFRICA Seagate Technology SAS 16-18 rue du Dôme, 92100 Boulogne-Billancourt, France, +33 1 41 86 10 00

© 2014 Seagate Technology LLC. All rights reserved. Printed in USA. Seagate, Seagate Technology and the Wave logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. PowerChoice is either a trademark or registered trademark of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. The FIPS logo is a certification mark of NIST, which does not imply product endorsement by NIST, the US or Canadian governments. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes; and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Actual data rates may vary depending on operating environment and other factors. The export or re-export of hardware or software containing encryption may be regulated by the US Department of Commerce, Bureau of Industry and Security (for more information, visit [www.bis.doc.gov](http://www.bis.doc.gov)), and controlled for import and use outside of the USA. Seagate reserves the right to change, without notice, product offerings or specifications. DS1791.6-1406GB, June 2014