EXOS X16 - 16TB



Sustainability Report*



Sustainability @ Seagate

Seagate is committed to sustainable storage. Our engineering focus is on increasing storage capacity and utilization, while controlling the quantity and types of materials we use and improving energy efficiency and recyclability.

Sustainable Design Features


- PowerBalance[™] feature optimizes Watts/TB
- Maximize total cost of ownership savings through lower power and weight with helium sealed-drive design


Energy and Greenhouse Gases

Manufacturing and using our products requires energy and produces Greenhouse Gas (GHG) emissions. We assess life cycle energy and GHG impacts and work towards improving energy and GHG efficiency and reducing ownership costs with each new generation of our products. Since 2022, our manufacturing facilities have operated using 100% renewable energy.

Power Consumption	Per Unit	Per TB
Average Idle Power (W)	5.1	0.3
Operating (W)	10.0	0.6
Average Annual (kWh)	45.6	2.9

Greenhouse Gas Emissions by Life Cycle Stage






Safer Materials

As a leading supplier to major original equipment manufacturers, Seagate helps to establish standards for direct materials – components that make up our products -- to meet customers' strictest specifications. We are meticulous about cataloging restricted substances; currently we list more than 2,000.


Human Toxicity by Life Cycle Stage




Scarce Resources

We aim to reduce our use of scarce resources during the life cycle of our products. We assess the water and mineral resource depletion impacts of our products in order to minimize dependence on key natural resources and reduce manufacturing and product ownership costs.

Mineral Resource Scarcity by Life Cycle Stage




Use Phase - Renewable Energy



Water Consumption by Life Cycle Stage

Use Phase - Conventional Energy 29.5% **Bill of Materials** 5.4% Manufacturing 0.1% Packaging 0.024 0.0% Distribution m³/TB-yr 65.0% Use Phase 0.0% End of Life



Materials Efficiency and Circularity

Seagate recognizes the traditional "take, make, dispose" linear approach to business is unsustainable. We measure our progress towards a circular economy with a variety of indicators including material used per TB of storage, use of recycled content, reuse rates, and recycling type and efficiency.

Device Weight - Shipped (g)		Per Unit	Per TB
Drive	Enclosure	514	32
	Media	137	9
	Electronics	16	1
Packaging	Cardboard and paper	55	3
	Other materials	19	1
Total		741	46

Materials Circularity Indicator

0%	25.8%	100%
Key Circularity Parameters		Per Unit
Estimated Operating Life		5 years
Recycled aluminum in base p	late	World average
Recycled aluminum in other	parts	World average
Recycled steel content		World average
Recycled cardboard		100%
Reused content		zero
Recycling rate		25%
Residual disposal		100% landfill
Reuse rate		zero
Recycling efficiency		95%
Recycling collections efficiency		90%

Seagate measures and reports its product sustainability performance on a TB-year basis. Seagate's drives come in different storage sizes and have different estimated useful lives. When referring to drive capacity, one terabyte, or TB, equals one trillion bytes. The TB-year measure combines these factors so that sustainability performance data is comparable across products and that annual impacts are directly reported. Seagate uses the Ecoinvent 3.8 Life Cycle Inventory database.

Seagate's sustainability assessment tools used to generate life cycle assessment results have been verified by UL in accordance with ISO 14040, ISO 14044, and the World Resources Institute and World Business Council for Sustainable Development's GHG Protocol Product Life Cycle Accounting and Reporting Standard.

© 2021 Seagate Technology LLC. All rights reserved. Printed in USA. Seagate, Seagate Technology and the Wave logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. Seagate reserves the right to change, without notice, product offerings or specifications. DS1663.4-0911US, March 2016