



DATA SHEET

Explosive Speed. Absolute Domination.

FireCuda 530 SSD

Blistering performance and unrivaled endurance—Seagate®

FireCuda[®] 530 redefines *speed*—up to 7,300MB/s catalyzes PCIe[®] Gen4 power. With transfer rates 2× faster than PCIe Gen3, FireCuda 530 is built for sustained abuse and dependable performance. The speed of PCIe Gen4 is yours—seize the power.







Best-Fit Applications

- High-performance gaming desktops
- · Creative professional systems



Key Advantages

Speed Reigns. FireCuda 530 dominates the SSD lineup—delivering pure performance, absolute power, the most advanced components, and unrivaled endurance.

Absolute Performance. At up to 7,300MB/s you can harness the full power of PCIe Gen4 speeds while DirectStorage support brings improved load times and performance to the next-generation games and applications.

Plug and Play Expansion for PS5 Compatible with PS5 consoles and meets PS5 performance and dimension specs for an ultra fast expansion solution.¹.

Fastest. FireCuda. Ever. Built for sustained, pro-level gaming and accelerated content creation with transfer speeds up to 2× faster than PCIe Gen3 NVMe SSDs and up to 12× faster than SATA SSDs.

Latest Tech. Built with a Seagate-validated E18 controller and the latest 3D TLC SSD NAND to provide the most advanced speed and durability.

Endurance Unleashed. Up to 5100TB TBW means you can write and delete 70% of the drive capacity, every day, for five years.

Considerable Capacity. Up to 4TB capacities keeps your gaming library at your fingertips and your creative content rendering.

Game and Create. Blistering transfer speeds of up to 7300MB/s, endurance, and capacity makes content creation apps run faster and smoother.

Rescue Services. Three years of Rescue Data Recovery Services, offering an industry-leading 95% success rate against unexpected data loss.

1 Using an M.2 SSD with your PS5 console requires effective heat dissipation with a cooling structure, such as an heatsink and a heat transfer sheet.

2 Rescue Data Recovery Services not available in all countries.







Specifications	FireCuda 530							
Capacity	4TB	2TB	1TB	500GB				
Standard Model	ZP4000GM3A013	ZP2000GM3A013	ZP1000GM3A013	ZP500GM3A013				
Interface	PCle® Gen4 ×4 NVMe 1.4	PCle Gen4 ×4 NVMe 1.4	PCIe Gen4 ×4 NVMe 1.4	PCIe Gen4 ×4 NVMe 1.4				
NAND Flash Memory	3D TLC	3D TLC	3D TLC	3D TLC				
Form Factor	M.2 2280-D2	M.2 2280-D2	M.2 2280-S2	M.2 2280-S2				
Performance								
Sequential Read (Max, MB/s), 128KB2	7250MB/s	7300MB/s	7300MB/s	7000MB/s				
Sequential Write (Max, MB/s), 128KB2	6900	6900	6000	3000				
Random Read (Max, IOPS), 4KB QD32 T8 ²	1000000IOPS	1000000IOPS	1000000IOPS	1000000IOPS				
Random Write (Max, IOPS), 4KB QD32 T82	1,000,000	1,000,000	1,000,000	1,000,000				
Endurance/Reliability								
Total Bytes Written (TB)	5100	2550	1275	640				
Mean Time Between Failures (MTBF, hours)	1800000 hrs	1800000 hrs	1800000 hrs	1800000 hrs				
Rescue Data Recovery Services (years)3	3	3	3	3				
Warranty, Limited (years)	5	5	5	5				
Power Management								
Active Power, Average (W)	8.6W	7.8W	6.3W	6.0W				
Idle Power PS3, Average (mW)	30mW	25mW	20mW	15mW				
Low Power L1.2 mode (mW)	<5	<5	<5	<5				
Environmental								
Temperature, Operating Internal (°C)	0°C – 70°C	0°C – 70°C	0°C – 70°C	0°C – 70°C				
Temperature, Nonoperating (°C)	-40°C – 85°C	-40°C – 85°C	-40°C – 85°C	-40°C – 85°C				
Shock, Nonoperating: 0.5ms (Gs)	1500Gs	1500Gs	1500Gs	1500Gs				
Special Features								
TRIM	Yes	Yes	Yes	Yes				
S.M.A.R.T.	Yes	Yes	Yes	Yes				
Halogen Free	Yes	Yes	Yes	Yes				
RoHS Compliance	Yes	Yes	Yes	Yes				
Physical								
Length (mm/in, max)	80.15mm/3.155in	80.15mm/3.155in	80.15mm/3.155in	80.15mm/3.155in				
Width (mm/in, max)	22.15mm/0.872in	22.15mm/0.872in	22.15mm/0.872in	22.15mm/0.872in				
Height (mm/in, max)	3.58mm/0.140in	3.58mm/0.140in	2.23mm/0.087in	2.23mm/0.087in				
Weight (g/lb)	10.6g/0.023lb	10g/0.022lb	8.1g/0.017lb	7.7g/0.016lb				

¹ Fresh out of box (FOB) performance obtained on newly formatted drive. Performance may vary based on SSD's firmware version, system hardware, and configuration. Performance based on CrystalDiskMark v.7.0.0 ×64 on Windows 10 host with PCIe Gen4 motherboard.

2 Rescue Data Recovery Services not available in all countries.







Specifications							
Retail Packaging	Box Dimensions	Master Carton Dimensions	Pallet Dimensions				
Length (in/mm)	5.285in/134.25mm	5.079in/129mm	47.992in/1219mm				
Width (in/mm)	4.291in/109mm	10.945in/278mm	20in/508mm				
Depth (in/mm)	0.945in/24mm	6.654in/169mm	27.795in/706mm				
Weight (lb/kg)	0.137lb/0.062kg	2.028lb/0.92kg	104.808lb/47.54kg				
Quantities							
Boxes per Master Carton	10						
Master Cartons per Pallet	48						
Pallet Layers	4						

System Requirements

What's Included

- M.2 (M key) slot, PCle[®] G4 ×4 interface (backwards compatible with PCle
 Seagate[®] FireCuda[®] 530 SSD G3 interface)
- Windows[®] 10
- Linux

Region	Model Number	Capacity	Limited Warranty (years)	UPC Code	EAN Code	Multi-Pack UPC
ww	ZP500GM3A013	500GB	5	763649161746	8719706420419	10763649161743
ww	ZP1000GM3A013	1TB	5	763649161753	8719706420426	10763649161750
ww	ZP2000GM3A013	2TB	5	763649161760	8719706420433	10763649161767
ww	ZP4000GM3A013	4TB	5	763649161777	8719706420440	10763649161774

seagate.com

S S E A G A T E

© 2023 Seagate Technology LLC. All rights reserved. Seagate, Seagate Technology, and the Spiral logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. FireCuda and the FireCuda logo are either trademarks or registered trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. The PCIe word mark and/or PCIExpress design mark are registered trademarks and/or service marks of PCI-SIG. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Actual data rates may vary depending on operating environment and other factors, such as chosen interface and drive capacity. Seagate reserves the right to change, without notice, product offerings or specifications. DS2059.5-2310 AMER