

3.5 HARD DRIVE DATA SHEET

Smart. Safe. Secure.
Video-Optimized Storage



SkyHawk™ leverages Seagate's extensive experience in designing drives purpose-built for video applications.



Best-Fit Applications

- Network video recorders (NVR)
- Video DVRs



SKYHAWK
HEALTH



Key Advantages

ImagePerfect™ firmware is designed to ensure seamless video footage capture in 24x7 workloads¹ that record video from 64 HD cameras.

SkyHawk Health Management actively helps protect your video storage by focusing on prevention, intervention, and recovery options.² Included is RAID RapidRebuild™, which provides 3x faster volume rebuilds over traditional RAID rebuilds.

Unparalleled data protection with included Rescue Data Recovery Services plan, helping protect important video data with Seagate's in-house data recovery services.

RV sensors built in allow drives to maintain performance in multi-bay systems, giving customers the flexibility to scale their systems when more storage is needed.

ATA streaming support enables recordings from up to 64 HD cameras for smooth, uninterrupted footage.

1M hours MTBF, 3-year limited warranty³ represents an improved total cost of ownership (TCO) with reduced maintenance costs.

Lower power consumption means a reduction in heat emissions, which improves reliability in surveillance solutions. Tarnish-resistant components help protect drive from environmental elements, increasing field reliability.

¹ SkyHawk video drives are designed for always-on workloads of 180TB/year. For higher transaction workloads, see Seagate's enterprise-class drive offerings.

² Contact your Seagate sales representative for further information.

³ Seagate does not recommend operating at sustained extreme temperatures. Operating at higher temperatures will reduce useful life of the products.



Specifications	8TB	6TB	4TB	3TB	2TB
Standard Model Numbers with SRS	ST8000VX010	ST6000VX009	ST4000VX016	ST3000VX015	ST2000VX017
SkyHawk™ Health Management Included	Yes	Yes	Yes	Yes	Yes
Interface	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s
Recording Technology	CMR	CMR	CMR	CMR	CMR
Drive Design	Air	Air	Air	Air	Air
Features and Performance					
Drive Bays Supported	Up to 16	Up to 16	Up to 16	Up to 8	Up to 8
Cameras Supported	Up to 64	Up to 64	Up to 64	Up to 64	Up to 64
RV Sensors	Yes	Yes	Yes	-	-
Max Sustained Transfer Rate OD (MB/s)	180MB/s	180MB/s	180MB/s	180MB/s	180MB/s
Cache (MB)	256MB	256MB	256MB	256MB	256MB
Reliability/Data Integrity					
Tarnish Resistant	Yes	Yes	Yes	Yes	Yes
Load/Unload Cycles	600,000	600,000	600,000	600,000	600,000
Nonrecoverable Read Errors Rate, Max	1 per 10E14	1 per 10E14	1 per 10E14	1 per 10E14	1 per 10E14
Power-On Hours per year	8760	8760	8760	8760	8760
Workload Rate Limit (WRL) ¹	180	180	180	180	180
Mean Time Between Failures (MTBF) (hours)	1000000hr	1000000hr	1000000hr	1000000hr	1000000hr
Warranty, Limited (years) ²	3	3	3	3	3
Rescue Data Recovery Services (years) ³	3	3	3	3	3
Power Management					
Startup Current, Typical (12V, A)	1.8A	1.8A	1.8A	1.8A	1.8A
Average Operating Power (W)	5.3W	5.3W	3.7W	3.7W	3.7W
Idle Average (W)	3.4W	3.4W	2.5W	2.5W	2.5W
Standby Mode/Sleep Mode, Typical (W)	0.25W	0.25W	0.25W	0.25W	0.25W
Voltage Tolerance (5V)	±5%	±5%	±5%	±5%	±5%
Voltage Tolerance (12V)	±10%	±10%	±10%	±10%	±10%
Environmental/Temperature					
Operating (ambient, min °C)	0°C	0°C	0°C	0°C	0°C
Operating (drive reported, max °C) ⁴	65°C	65°C	65°C	65°C	65°C
Nonoperating (ambient, min °C)	-40°C	-40°C	-40°C	-40°C	-40°C
Physical					
Height (mm/in, max)	26.1mm/1.028in	26.1mm/1.028in	20.20mm/0.795in	20.20mm/0.795in	20.20mm/0.795in
Width (mm/in, max)	101.6mm/4.00in	101.6mm/4.00in	101.6mm/4.0in	101.6mm/4.0in	101.6mm/4.00in
Depth (mm/in, max)	146.99mm/5.787in	146.99mm/5.787in	146.99mm/5.787in	146.99mm/5.787in	146.99mm/5.787in
Weight (g/lb, typical)	630g/1.389lb	630g/1.389lb	630g/1.389lb	490g/1.08lb	415g/0.915lb
Carton Unit Quantity	20	20	25	25	25
Cartons per Pallet/Cartons per Layer	40/8	40/8	40/8	40/8	40/8

¹ SkyHawk surveillance drives are designed for always-on workloads of 180TB/year. For higher transaction workloads, see Seagate's enterprise-class drive offerings.

² Extended warranty options available. Consult your distributor for details.

³ From May 1, 2020, 3-year Rescue Data Recovery Services plan may be offered in addition to standard warranty. This is offered for selected regions only. Check with reseller on availability.

⁴ Seagate does not recommend operating at sustained extreme temperatures. Operating at higher temperatures will reduce useful life of the products.



Specifications	1TB
Standard Model Numbers with SRS	ST1000VX013
SkyHawk™ Health Management Included	Yes
Interface	SATA 6Gb/s
Recording Technology	CMR
Drive Design	Air
Features and Performance	
Drive Bays Supported	Up to 8
Cameras Supported	Up to 64
RV Sensors	-
Max Sustained Transfer Rate OD (MB/s)	180MB/s
Cache (MB)	256MB
Reliability/Data Integrity	
Tarnish Resistant	Yes
Load/Unload Cycles	600,000
Nonrecoverable Read Errors Rate, Max	1 per 10E14
Power-On Hours per year	8760
Workload Rate Limit (WRL) ¹	180
Mean Time Between Failures (MTBF) (hours)	1000000hr
Warranty, Limited (years) ²	3
Rescue Data Recovery Services (years) ³	-
Power Management	
Startup Current, Typical (12V, A)	1.8A
Average Operating Power (W)	3.7W
Idle Average (W)	2.5W
Standby Mode/Sleep Mode, Typical (W)	0.25W
Voltage Tolerance (5V)	±5%
Voltage Tolerance (12V)	±10%
Environmental/Temperature	
Operating (ambient, min °C)	0°C
Operating (drive reported, max °C) ⁴	65°C
Nonoperating (ambient, min °C)	-40°C
Physical	
Height (mm/in, max)	20.20mm/0.795in
Width (mm/in, max)	101.6mm/4.00in
Depth (mm/in, max)	146.99mm/5.787in
Weight (g/lb, typical)	415g/0.915lb
Carton Unit Quantity	25
Cartons per Pallet/Cartons per Layer	40/8

¹ SkyHawk surveillance drives are designed for always-on workloads of 180TB/year. For higher transaction workloads, see Seagate's enterprise-class drive offerings.

² Extended warranty options available. Consult your distributor for details.

³ From May 1, 2020, 3-year Rescue Data Recovery Services plan may be offered in addition to standard warranty. This is offered for selected regions only. Check with reseller on availability.

⁴ Seagate does not recommend operating at sustained extreme temperatures. Operating at higher temperatures will reduce useful life of the products.

© 2021 Seagate Technology LLC. All rights reserved. Seagate, Seagate Technology, and the Spiral logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. ImagePerfect, RAID RapidRebuild, SkyHawk, and the SkyHawk logo are either trademarks or registered trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Quantitative usage examples for various applications are for illustrative purposes. Actual quantities will vary based on various factors, including file size, file format, features, and application software. Actual data rates may vary depending on operating environment and other factors, such as chosen interface and disk capacity. Seagate reserves the right to change, without notice, product offerings or specifications. DS1902.17-2107US July 2021