

Data Sheet

Momentum 5400.3

The freedom of mobility and enhanced productivity with 5400-RPM performance

160, 120, 100, 80, 60 and 40 GB • 5400-RPM Performance • 2.5-Inch Laptop

Key Advantages

- Nearly 50 percent more performance than systems with 4200-RPM drives
- 4200-RPM-like battery consumption enables higher productivity.
- Robust design and high shock tolerance enable mobility in rugged laptop operating environments.
- 350 Gs of operating shock and 900 Gs of nonoperating shock make the drive ideal for laptop PCs and industrial applications.
- Best-in-class 5400-RPM laptop performance

Best-Fit Applications

- Mainstream laptop PCs
- Tablet PCs
- External 2.5-inch drives
- MP3 players
- Printers and copiers



Momentum 5400.3

The freedom of mobility and enhanced productivity with 5400-RPM performance



The Momentum 5400.3 drive is the first Seagate product to utilize perpendicular recording technology. This innovative technology enables Seagate to deliver the industry's highest capacity of 160 GB in a single, 2.5-inch hard drive without sacrificing best-in-class features.

Seagate Global Customer Support

- Get presales and technical support at support.seagate.com.
- Visit our knowledge base for answers to common support questions.
- Find documentation for current and legacy drives.
- Utilize our online troubleshooting and diagnostic tools.
- Download DiscWizard™ to help migrate data from an older drive.
- Seagate also offers multi-lingual phone, email and chat support.
- Seagate Design Service Centers (DSC) help companies transform innovative ideas into viable products.

www.seagate.com

1-800-SEAGATE (1-800-732-4283)

Specifications	160 GB ¹	120 GB ¹	100 GB ¹	80 GB ¹	60 GB ¹	40 GB ¹
Model Number	ST9160821A ST9160821AS	ST9120822A ST9120822AS	ST9100828A ST9100828AS	ST980815A ST980811AS	ST960815A ST960813AS	ST940815A ST940814AS
Interface	ATA SATA w/NCQ	ATA SATA w/NCQ	ATA SATA w/NCQ	ATA SATA w/NCQ	ATA SATA w/NCQ	ATA SATA w/NCQ
Performance						
Transfer Rate						
Sustained Internal (MB/s)	44	44	44	44	44	44
Maximum External (MB/s)	100/150	100/150	100/150	100/150	100/150	100/150
Cache, Multisegmented (MB)	8	8	8	8	8	8
Average Seek (ms)	12.5/13.0	12.5/13.0	12.5/13.0	12.5/13.0	13.0	12.5/13.0
Average Latency (ms)	5.6	5.6	5.6	5.6	5.6	5.6
Performance Level	5400	5400	5400	5400	5400	5400
Configuration/Organization						
Disks/Heads	2/4	2/3	2/3	1/2	1/2	1/1
Bytes per Sector	512	512	512	512	512	512
Logical CHS	92,049/16/63	92,049/16/63	92,049/16/63	92,049/16/63	92,049/16/63	92,049/16/63
Recording Method	Perpendicular	Perpendicular	Perpendicular	Perpendicular	Perpendicular	Perpendicular
Reliability/Data Integrity						
Head-Rest Method	QuietStep™ Ramp Load	QuietStep Ramp Load	QuietStep Ramp Load	QuietStep Ramp Load	QuietStep Ramp Load	QuietStep Ramp Load
Load/Unload Cycles	>600,000	>600,000	>600,000	>600,000	>600,000	>600,000
Nonrecoverable Read Errors per Bits Read	1 per 10E14	1 per 10E14	1 per 10E14	1 per 10E14	1 per 10E14	1 per 10E14
Power Management						
Startup Current 5v (amps max)	1.0	1.0	1.0	1.0	1.0	1.0
Power Management (watts)						
Seek	2.0	2.0	2.0	2.0	2.0	2.0
Read/Write, PATA	2.0/1.8	2.0/1.8	2.0/1.8	2.0/1.8	2.0/1.8	2.0/1.8
Read/Write, SATA	1.9/1.8	1.9/1.8	1.9/1.8	1.9/1.8	1.9/1.8	1.9/1.8
Idle/Standby, PATA	0.8/0.2	0.8/0.2	0.8/0.2	0.8/0.2	0.8/0.2	0.8/0.2
Idle/Standby, SATA	0.6/0.2	0.6/0.2	0.6/0.2	0.6/0.2	0.6/0.2	0.6/0.2
Environmental						
Temperature, Operating (°C)	0 to 60	0 to 60	0 to 60	0 to 60	0 to 60	0 to 60
Temperature, Nonoperating (°C)	-40 to 70	-40 to 70	-40 to 70	-40 to 70	-40 to 70	-40 to 70
Shock, Operating: 2 ms (Gs)	350	350	350	350	350	350
Shock, Nonoperating: 1 ms (Gs)	900	900	900	900	900	900
Acoustics (bels—sound power)						
Idle	2.4	2.4	2.4	2.4	2.4	2.4
Performance Seek	3.0	3.0	3.0	3.0	3.0	3.0
Physical						
Height (in/mm)	0.374/9.5	0.374/9.5	0.374/9.5	0.374/9.5	0.374/9.5	0.374/9.5
Width (in/mm)	2.75/69.85	2.75/69.85	2.75/69.85	2.75/69.85	2.75/69.85	2.75/69.85
Depth (in/mm)	3.957/100.5	3.957/100.5	3.957/100.5	3.957/100.5	3.957/100.5	3.957/100.5
Weight, PATA (lb/g)	0.22/102	0.22/102	0.22/102	0.216/98	0.216/98	0.216/98
Weight, SATA (lb/g)	0.22/100	0.22/100	0.22/100	0.21/96	0.21/96	0.21/96

¹ One gigabyte, or GB, equals one billion bytes when referring to hard drive capacity.

AMERICAS Seagate Technology LLC 920 Disc Drive, Scotts Valley, California 95066, United States, 831-438-6550
 ASIA/PACIFIC Seagate Technology International Ltd. 7000 Ang Mo Kio Avenue 5, Singapore 569877, 65-6485-3888
 EUROPE, MIDDLE EAST AND AFRICA Seagate Technology SAS 130-136, rue de Sully, 92773, Boulogne-Billancourt Cedex, France 33 1-4186 10 00

Copyright © 2008 Seagate Technology LLC. All rights reserved. Printed in USA. Seagate, Seagate Technology and the Wave logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. Momentum and QuietStep are either trademarks or registered trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks are the property of their respective owners. When referring to hard drive capacity, one gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Seagate reserves the right to change, without notice, product offerings or specifications. DS1598.4-0812US, December 2008