



Technology Paper

Seagate® PowerChoice™ Technology Provides Unprecedented Hard Drive Power Savings and Flexibility

Introduction

While the challenging economic climate continues to exert downward pressure on enterprise IT investment, there is one key exception to this trend. According to research company Gartner, Inc., storage spending is growing almost three times faster than IT budgets as a whole. From 2007 to 2011, storage expenditures will increase more than 7 per cent per year, compared with annual IT budget growth of only 2.5 per cent, states John Monroe, Gartner vice president.

But this impressive growth in storage spending, fuelled by relentless demand for more capacity and greater speed, comes at a time when companies of all sizes are striving to cut IT energy costs significantly. Notes John Monroe, a research vice president at Gartner, "The need for greater storage capacity will continue to expand in multiple directions and dimensions, but there will be an increasing scrutiny of all storage system purchases, with an eye to decreasing power consumption, footprint and cost per GB in unprecedented ways."

Achieving the diverse goals of abundant capacity, high performance, low cost per GB and reduced power consumption poses a daunting task for any hard drive manufacturer. Seagate Technology is uniquely suited to meet this challenge, exploiting its industry-leading innovation and engineering expertise to create Seagate PowerChoice technology. Simply put, PowerChoice technology drive power management delivers the lowest power usage ever offered in an enterprise-class hard drive.

Raising the Bar for Power Reduction

Recent years have seen data centre power and cooling costs rise dramatically, spurring technology manufacturers to implement a variety of innovative power-saving features in their products. Seagate spearheaded the movement towards more energy-efficient hard drives with its PowerTrim™ technology, which has been used throughout Seagate enterprise-class hard drive families.

Seagate® PowerChoice™ Technology Provides Unprecedented Hard Drive Power Savings and Flexibility



Now Seagate has taken hard drive power management to the next level with its new PowerChoice technology (a proprietary implementation of T10 Approved Standard No T10/09-054 and T13 Standard No T13/452-2008), delivering an unprecedented combination of energy efficiency and user flexibility.

First to market, Seagate has made significant contributions to the new cost-saving standard developed and published by the T10/T13 committees and currently offers PowerChoice technology on the Savvio® (starting with Savvio 10K.4), Constellation™ and Constellation ES enterprise-class hard drives.

While PowerTrim technology is an automatic power-saving feature that is activated during very brief periods of command inactivity, without impacting performance, PowerChoice technology complements PowerTrim technology by enabling even greater power reductions with four modes that cover idle periods greater than one second. The result? PowerChoice technology decreases drive power consumption by up to 54 per cent in enterprise environments.

Moreover, PowerChoice technology enables the host to tailor the drive's power-saving settings for performance and power consumption via mode pages (SAS/FC) or Set Features commands (SATA). This configuration flexibility ensures that users can specify the optimal idling time thresholds for their particular storage applications. In addition to allowing the host to control the drives, with

PowerChoice technology enable/disable and timer mode page settings, the host can take full control of the PowerChoice technology capabilities via the Start/Stop Unit (SSU) command (SAS/FC) or Set Feature commands (SATA), thereby disabling the drives' timer-based controls and allowing host-directed power transitions to occur immediately.

Benefits of PowerChoice Technology

Purpose-built for enterprise environments, PowerChoice technology made its debut in the new Constellation family of nearline enterprise hard drives. These high-capacity, 7,200-RPM drives (2.5-inch Constellation and 3.5-inch Constellation ES drives, in both SAS and SATA interfaces) are optimised for Tier-2/nearline applications, which demand enormous capacity and enterprise-class reliability under the less rigorous workloads that characterise nearline environments.

For environments where hard drives are idling more frequently and for longer periods, the benefits of the Constellation family of drives are particularly compelling. (PowerChoice technology is now also available in Seagate Savvio 10K mission-critical drives.) As may be seen in the table below, the drive's power savings significantly increase as idling time grows. It is important to note that such power savings are achieved while ensuring that the drive can still respond promptly to commands, thus preventing any degradation of system performance.

PowerChoice™ Technology Profile: Constellation™ 2.5-inch Drive Power Savings and Response Time				
	Power (W)	Power Savings ¹ (%)	Recovery Time (sec)	Default Timer to Entry
Idle	2.82	0	0	n/a
Idle_A	2.82	0	0	1 sec
Idle_B	2.18	23	0.5	10 min
Idle_C	1.82	35	1	30 min
Standby_Z	1.29	54	8	60 min

¹ Power savings estimates and recovery times are preliminary; figures based on Seagate® Constellation SAS 2.5-inch hard drive

Seagate® PowerChoice™ Technology Provides Unprecedented Hard Drive Power Savings and Flexibility



Clearly, the power savings of PowerChoice technology-equipped hard drives are substantial. For example, a 1U rack filled with twenty-four 500 GB Constellation drives that have entered PowerChoice technology C mode delivers 12 TB of storage, yet consumes only 43W or slightly more power than a single 40W light bulb!

How PowerChoice Technology Works

Each individual power condition builds on the capabilities of the previous higher power condition in order to save incrementally more power. The specific energy-saving steps implemented for each power condition are as follows:

Idle_A

- Disables most of the servo system, reduces processor and channel power consumption
- Discs rotating at full speed (7,200 RPM)

Idle_B

- Disables most of the servo system, reduces processor and channel power consumption
- Heads are unloaded to drive ramp.
- Discs rotating at full speed (7,200 RPM)

Idle_C/Standby_Y (SAS Only)

- Disables most of the servo system, reduces processor and channel power consumption
- Heads are unloaded to drive ramp.
- Drive speed reduced to a lower RPM (reduced RPM)

Standby_Z

- Heads are unloaded to drive ramp.
- Drive motor is spun down.
- Drive still responds to non-media access host commands.

As noted earlier, flexibility is a key feature of PowerChoice technology, enabling commands from the host side to customise power condition settings and direct a drive into or out of power conditions as required. Two different options are available for the user to modify PowerChoice technology settings, depending on the interface used:

SAS

- Host-definable timers via mode pages
- Immediate host-commanded power transitions via Start/Stop Unit (SSU) command

SATA

- Host-definable timers via Set Features commands
- Immediate host-commanded power transitions via Set Features commands

Conclusion

With ever-tightening IT budgets and growing concerns over both the fiscal and environmental costs of escalating power use, the need for more energy-efficient storage in the enterprise has never been more urgent. Seagate has responded with the Constellation and Savvio 10K families of enterprise-class hard drives featuring PowerChoice technology, and in so doing has rewritten the rules for high-capacity storage in the data centre.

Not only do these drives boast remarkably low operating power needs, the enhanced power options enabled by PowerChoice technology reduce energy costs even further during slow or idle periods. As a result, these models deliver the highest power-reduction savings ever offered in an enterprise-class drive. Moreover, PowerChoice technology's flexible, user-manageable options enable these power savings without sacrificing performance, data integrity or reliability.

Featuring the world's first 2.5-inch, 7,200 RPM nearline hard drive, the industry's first 10K RPM, 600 GB drive and a range of 3.5-inch drives that offer capacities up to 2 TB, the Constellation and Savvio 10K families are made even more compelling by the inclusion of PowerChoice technology. With its blend of significant power savings and easy user configurability, PowerChoice technology has raised the bar for energy-efficient enterprise storage.

Seagate® PowerChoice™ Technology Provides Unprecedented Hard Drive Power Savings and Flexibility



Appendix – Implementation Guide

The following details simplify integration of the PowerChoice technology feature set for deployment in enterprise system architectures. As already mentioned, the Seagate PowerChoice technology feature is available on SAS, FC and SATA interfaces. The following information details the implementation guidelines for SAS and SATA interfaces.

Serial Attached SCSI (SAS) Command Implementation

The following details provide the information required to determine which features the drive supports, how to enable/disable and modify the power condition timers, interpret sense code responses, access log pages detailing PowerChoice technology-related activity, and how the host can initiate direct control of PowerChoice technology savings via the Start/Stop Unit (SSU) command.

The SAS implementation allows the host to control staggered spin-up for each device to recover from Standby_Y or Standby_Z using the SAS Notify (Enable Spin-up) primitive. When Standby_Y or Standby_Z is used, the drive requires two events to occur before transitioning to the active state. The sequence of events required to enter the active state from a Standby_Y condition is a media access request from the host followed by receipt of the Notify (Enable Spin-up) primitive. The drive waits indefinitely after receipt of a media access command for the Notify (Enable Spin-up) primitive.

Determining Capabilities Supported by PowerChoice Technology

PowerChoice technology capabilities are reported via the Vital Product Data (VPD) page 8Ah. This page reports the power conditions supported by PowerChoice technology:

Bit	7	6	5	4	3	2	1	0
0	Peripheral Qualifier			Peripheral Device Type				
1	Page Code (8Ah)							
2	Reserved							
3	Page Length (0Eh)							
4	Reserved					STANDBY_Y		STANDBY_Z
5	Reserved				IDLE_C	IDLE_B	IDLE_A	
6 - 7	STOPPED CONDITION RECOVERY TIME							
8 - 9	STANDBY_Z CONDITION RECOVERY TIME							
10 - 11	STANDBY_Y CONDITION RECOVERY TIME							
12 - 13	IDLE_A CONDITION RECOVERY TIME							
14 - 15	IDLE_B CONDITION RECOVERY TIME							
16 - 17	IDLE_C CONDITION RECOVERY TIME							

Notes.

- Byte 4 bits 0 – 1 report support for Standby power conditions.
- Byte 5 bits 0 – 2 report support for Idle power conditions.
- Bytes 6 – 7 report the typical power-on time in 1-ms increments.
- Bytes 8 – 17 report the typical recovery time in 1-ms increments for the associated power condition.
- A bit value of 1 in bytes 4 or 5 indicates support for the associated power condition.
- A value of 0 for the associated power condition indicates that support does not exist.

Seagate® PowerChoice™ Technology Provides Unprecedented Hard Drive Power Savings and Flexibility



Determining or Modifying PowerChoice Technology Settings

Analysing and changing PowerChoice technology settings is done via the SCSI Mode Sense and Mode Select commands. The Mode Sense command is used to report the current PowerChoice technology settings by accessing mode page 1Ah:

Byte \ Bit	7	6	5	4	3	2	1	0
0	PS	SPF(0b)		Page Code (1Ah)				
1	Page Length							
2	Reserved							STANDBY_Y
3	Reserved				IDLE_C	IDLE_B	IDLE_A	STANDBY_Z
4 - 7	IDLE_A CONDITION TIMER							
8 - 11	STANDBY_Z CONDITION TIMER							
12 - 15	IDLE_B CONDITION TIMER							
16 - 19	IDLE_C CONDITION TIMER							
20 - 23	STANDBY_Y CONDITION TIMER							
24 - 39	RESERVED							

Notes

The behaviour of PS and SPF bits is defined by the SPC-4 standard.
 Byte 2 bit 0 and byte 3 bits 0 – 3 indicate whether the associated power condition is enabled or disabled.
 A bit equal to 1 indicates that the associated power condition is enabled.
 A bit equal to 0 indicates that the associated power condition is disabled.

Idle_C and Standby_Y are mutually exclusive; only one may be enabled at a time. Both power conditions place the drive in a state where the heads are parked on the ramp while the spindle speed is reduced to a lower RPM, the difference being how the drive returns to the active power state. If the Idle_C power condition is enabled, then the drive returns to the active state upon receipt of any media access command. If the Standby_Y power condition is enabled, then the drive requires two events to return to the active state: first, receipt of a media access command, which must be followed by receipt of a Notify (Enable Spin-up) primitive. Use of Standby_Y allows the host to stagger spin-up of drives within an enclosure. The drive waits indefinitely for receipt of the Notify (Enable Spin-up) primitive. This behaviour is equivalent to issuing a SCSI Start command or initial drive spin-up from a powered-off state.

Seagate® PowerChoice™ Technology Provides Unprecedented Hard Drive Power Savings and Flexibility



Bytes 4 – 23 define the time in 100-ms increments that the drive waits after the command queue is empty before transitioning to the associated power condition. The Default mode page reports the minimum timer value; each power condition timer may be set with a Mode Select command. Each minimum timer value is established at the time of manufacture, prior to dispatch.

The host system can set any of the power condition timers to a value greater than the default by using the Mode Select command. New values for the timers can be set individually or at the same time. Attempts to set the timer values to less than the default results in an error being reported by the drive, as per the standard reporting method defined by the SPC-4 standard.

The drive enters each power condition as the associated timer expires. If multiple timers expire at the same time, the drive enters the power condition with the greatest amount of power savings.

Host Control of Power Conditions

To allow unlimited flexibility in controlling the drive's PowerChoice technology feature, the Start/Stop Unit (SSU) SCSI command can be used. This allows the host system to take full control of PowerChoice technology, initiating direct power transition or allowing the drive's automated timer controls to execute. Various combinations of the SSU command are available and provide the host with the following capabilities:

- Cause transition to the active condition
- Cause transition to an Idle power condition
- Cause transition to a Standby power condition
- Force an Idle power condition timer to expire
- Force a Standby power condition timer to expire
- Initialise and start all enabled Idle power condition timers
- Initialise and start all enabled Standby power condition timers

The host uses the SSU command Power Condition and Power Condition Modifier fields to control PowerChoice technology's capabilities listed above. The SSU command is defined as follows:

Byte \ Bit	7	6	5	4	3	2	1	0
0	OPERATION CODE (1Bh)							
1	Reserved							IMMED
2	Reserved							
3	Reserved				POWER CONDITION MODIFIER			
4	POWER CONDITION				Reserved	N FLUSH	LOEJ	START
5	CONTROL							

Notes

The behaviour of all bits in the SSU command is defined by the SPC-4 standard, except for the Power Condition and Power Condition Modifier fields.

Seagate® PowerChoice™ Technology Provides Unprecedented Hard Drive Power Savings and Flexibility



Definitions of the Power Condition and Power Condition Modifier fields are described in the table below:

Power Condition Value	Power Condition Modifier Value	Description
0h	0h	Process the START and LOEF bits.
1h	0h	Cause the drive to transition to the active power condition
2h	0h	Cause the drive to transition to the Idle_A power condition
	1h	Cause the drive to transition to the Idle_B power condition
	2h	Cause the drive to transition to the Idle_C power condition
3h	0h	Cause the drive to transition to the Standby_Z power condition
	1h	Cause the drive to transition to the Standby_Y power condition
7h	0h	Initialise and start all of the Idle and Standby timers that are enabled
Ah	0h	Force the Idle_A power condition timer to expire
	1h	Force the Idle_B power condition timer to expire
	2h	Force the Idle_C power condition timer to expire
Bh	0h	Force the Standby_Z power condition timer to expire
	1h	Force the Standby_Y power condition timer to expire

Receipt of any SSU command with a non-zero value in the Power Condition field results in all power condition timers being disabled. The timers remain disabled until receipt of an SSU command to initialise and start all timers or upon receipt of a logical unit reset.

Receipt of any SSU command with the Power Condition field set to 2h or 3h causes the drive to transition to the specified power condition immediately. If the requested power condition results in greater power savings, the drive transitions directly to that power condition. If the request causes the drive to transition to a power condition that increases power used, then the drive transitions to the Active Condition first, followed by a transition to the requested power condition.

Receipt of any SSU command with the Power Condition field set to Ah or Bh may cause the drive to transition to a greater power-saving condition. If the drive is in Idle_C and the SSU command requests the Idle_B power condition timer to expire, the drive remains in the Idle_C Power Condition.

Seagate® PowerChoice™ Technology Provides Unprecedented Hard Drive Power Savings and Flexibility



Determining the Current Power State of the Drive

To allow the host to determine whether the drive is in a power condition, a SCSI Request Sense command may be issued. Receipt of a Request Sense command does not change the current power state of the drive. If the drive is currently in a power condition, the reported sense code is as shown:

Sense Key	ASCQ	Description
5Eh	00h	LOW POWER CONDITION ON
5Eh	01h	IDLE CONDITION ACTIVATED BY TIMER
5Eh	02h	STANDBY CONDITION ACTIVATED BY TIMER
5Eh	03h	IDLE CONDITION ACTIVATED BY COMMAND
5Eh	04h	STANDBY CONDITION ACTIVATED BY COMMAND
5Eh	05h	IDLE_B CONDITION ACTIVATED BY TIMER
5Eh	06h	IDLE_B CONDITION ACTIVATED BY COMMAND
5Eh	07h	IDLE_C CONDITION ACTIVATED BY TIMER
5Eh	08h	IDLE_C CONDITION ACTIVATED BY COMMAND
5Eh	09h	STANDBY_Y CONDITION ACTIVATED BY TIMER
5Eh	0Ah	STANDBY_Y CONDITION ACTIVATED BY COMMAND

In addition to indicating the drive's current power condition, the sense code also indicates the method used by the drive to enter the current power condition. As already discussed, the drive may enter a given power condition via expiry of the defined mode page timers or as a result of receiving an SSU command from the host.

Power Condition Transitions Log Page

Log page 1Ah provides a counter to record each time the drive transitions into a particular target condition. The following table defines the parameter codes associated with each power condition transition:

Parameter Code	Description
0000h	Accumulated Transitions to Active
0001h	Accumulated Transitions to Idle_A
0002h	Accumulated Transitions to Idle_B
0003h	Accumulated Transitions to Idle_C
0008h	Accumulated Transitions to Standby_Z
0009h	Accumulated Transitions to Standby_Y

The payload response received when issuing a Log Select command to the drive requesting all parameter codes defined in the above table would be as shown in the table on the following page.

Seagate® PowerChoice™ Technology Provides Unprecedented Hard Drive Power Savings and Flexibility



Byte \ Bit	7	6	5	4	3	2	1	0
0	DS	SPF (0b)	Page Code (1Ah)					
1	Subpage Code (00h)							
2	(MSB)				Page Length (30h)			
3	(LSB)							
4	(MSB)	PARAMETER CODE (0000h)						
5	Accumulated transitions to active state							(LSB)
6	DU	Obsolete	TSD	ETC	TMC	FMT & LINKING		
7	Parameter Length (04h)							
8	(MSB)	Accumulated Transitions to Active						
11	(4-byte binary number)							(LSB)
12	(MSB)	Parameter Code (0001h)						
13	Accumulated transitions to Idle_A state							(LSB)
14	DU	Obsolete	TSD	ETC	TMC	FMT & LINKING		
15	Parameter Length (04h)							
16	(MSB)	Accumulated Transitions to Idle_A						
19	(4-byte binary number)							(LSB)
20	(MSB)	Parameter Code (0002h)						
21	Accumulated Transitions to Idle_B State							(LSB)
22	(DU)	Obsolete	TSD	ETC	TMC	FMT & LINKING		
23	Parameter Length (04h)							
24	(MSB)	Accumulated Transitions to Idle_B						
27	(4-byte binary number)							(LSB)
28	(MSB)	Parameter Code (0003h)						
29	Accumulated Transitions to Idle_C State							(LSB)
30	(DU)	Obsolete	TSD	ETC	TMC	FMT & LINKING		
31	Parameter Length (04h)							
32	(MSB)	Accumulated Transitions to Idle_C						
35	(4-byte binary number)							(LSB)
36	(MSB)	Parameter Code (0008h)						
37	Accumulated Transitions to Standby_Z State							(LSB)
38	(DU)	Obsolete	TSD	ETC	TMC	FMT & LINKING		
39	Parameter Length (04h)							
40	(MSB)	Accumulated Transitions to Standby_Z						
43	(4-byte binary number)							(LSB)
44	(MSB)	Parameter Code (0009h)						
45	Accumulated Transitions to Standby_Y State							(LSB)
46	DU	Obsolete	TSD	ETC	TMC	FMT & LINKING		
47	Parameter Length (04h)							
48	(MSB)	Accumulated Transitions to Standby_Y						
51	(4-byte binary number)							(LSB)

A count is defined as a transition from one power condition to a target power condition. A request to transition to a power condition that the drive is presently in does not increment the counter for that power condition. All counters are saturating counters and do not reset or roll over.

Seagate® PowerChoice™ Technology Provides Unprecedented Hard Drive Power Savings and Flexibility



Start/Stop Cycle Counter Log Page

Log page 0Eh has been extended to include two additional items, drive “Specified Load-Unload Count Over Device Lifetime” (parameter code 0005h) and “Accumulated Load-Unload Cycles” (parameter code 0006h). The specified count is a fixed value and provides the user with a means to determine the drive’s load-unload cycle capability. The accumulated load-unload counter provides real-time determination of how many load-unload cycles the drive has completed. The accumulated count includes all load-unload cycles resulting from the drive being powered on and off or the result of a transition to a power condition. All counters are saturating counters and do not reset or roll over.

A load-unload cycle is defined as an operational cycle with the heads unloaded from the medium: it continues while the heads are loaded on to the spinning medium and ends when the heads are unloaded from the medium.

The payload response received when issuing a Log Select command to the drive requesting parameter codes 0005h and 0006h returns the following:

Byte	Bit	7	6	5	4	3	2	1	0
0		DS	SPF(0b)	Page Code (0Eh)					
1		SUBPAGE CODE (00h)							
2	(MSB)	PAGE LENGTH (0052h)							
3		(LSB)							
4		Bytes previously defined (See SCSI Command Manual)							
:									
39									
40	(MSB)								
41		Specified load-unload count over device lifetime							(LSB)
42		DU	Obsolete	TSD	ETC	TMC	FMT & LINKING		
43		PARAMETER LENGTH (04h)							
44	(MSB)	SPECIFIED LOAD-UNLOAD COUNT OVER DEVICE LIFETIME							
47		(4-byte binary number)							(LSB)
48	(MSB)	PARAMETER CODE (0006h)							
49		Accumulated load-unload cycles							(LSB)
50		DU	Obsolete	TSD	ETC	TMC	FMT & LINKING		
51		PARAMETER LENGTH (04h)							
52	(MSB)	ACCUMULATED LOAD-UNLOAD CYCLES							
55		Accumulated load-unload cycles							(LSB)

Seagate® PowerChoice™ Technology Provides Unprecedented Hard Drive Power Savings and Flexibility



SCSI Command Interaction While in a Power Condition

Limited command capability is available if the drive is in a power condition. The following are the commands that the drive executes and returns a status for without causing a transition to the Active power state:

- Test Unit Ready
- Request Sense
- Report LUNs
- Start/Stop Unit

Note Use of the Start/Stop Unit (SSU) command may result in a transition to the Active state or a power condition as defined by the SSU commands Power Condition and Power Condition Modifier fields.

PowerChoice Technology Interaction with Background Drive Activities

The drive performs various background activities to update log pages and SMART information as well as maintaining the integrity of the data written to the media. With this in mind, PowerChoice technology works in unison with background activities. If any background activity is active when a power condition timer expires, entry into the power condition is held off until the required background activity is completed. During this waiting period, all power condition timers are suspended. If the transition to a target power condition is the result of an SSU command from the host, then the transition is held off until the background activity is completed.

If the drive is in the process of completing a BMS (Background Media Scan) cycle, then the drive responds to the SSU command with a sense code of 052C0005 (Illegal Power Condition Request). The host can monitor the progress of the current BMS cycle by issuing a Log Select command to return log page 15h (Background Scan Results) and evaluate the “Background Medium Scan Progress” field.

SATA Set Features Command

Extended Power Conditions – PowerChoice Technology

Using the load/unload architecture, a programmable power management interface is provided to tailor systems for reduced power consumption and performance requirements.

The table below lists the supported power conditions available in PowerChoice technology. Power conditions are ordered from highest power consumption (and shortest recovery time) to lowest power consumption (and longest recovery time) as follows: Idle_A power ≥ Idle_B power ≥ Idle_C power ≥ Standby_Z power. The further you go down in the table, the greater the power savings. For example, Idle_B results in greater power savings than the Idle_A power condition. Standby results in the greatest power savings.

Power Condition Name	Power Condition ID	Description
Idle_A	81h	Reduced electronics
Idle_B	82h	Heads unloaded; discs spinning at full RPM
Idle_C	83h	Heads unloaded; discs spinning at reduced RPM
Standby_Z	00h	Heads unloaded; motor stopped (discs not spinning)

Seagate® PowerChoice™ Technology Provides Unprecedented Hard Drive Power Savings and Flexibility



Each power condition has a set of current, saved and default settings. Default settings are not modifiable. Default and saved settings persist across power-on resets. The current settings do not persist across power-on resets. At the time of manufacture, the default, saved and current settings in the Power Conditions log match.

PowerChoice technology is invoked using one of two methods:

- Automatic power transitions, which are triggered by expiry of individual power condition timers. These timer values may be customised and enabled using the Extended Power Conditions (EPC) feature set using the standardised Set Features command interface.
- Immediate host-commanded power transitions may be initiated using an EPC Set Feature “Go to Power Condition” subcommand to enter any supported power condition. Legacy power commands Standby Immediate and Idle Immediate also provide a method to transition the drive directly into supported power conditions.

PowerChoice technology exits power saving states under the following conditions:

- Any command that requires the drive to enter the PM0: Active state (media access)
- Power-on reset

PowerChoice technology provides the following reporting methods for tracking purposes:

- Check Power Mode Command
 - Reports the current power state of the drive
- Identify Device Command
 - EPC Feature sets supported flag
 - EPC Feature enabled flag is set if at least one Idle power condition timer is enabled

Power Condition Log reports the following for each power condition:

- Nominal recovery time from the power condition to active
- If the power condition is Supported, Changeable and Savable
- Default enabled state and timer value
- Saved enabled state and timer value
- Current enabled state and timer value

SMART Read Data reports:

- Attribute 192 – Emergency Retract Count
- Attribute 193 – Load/Unload Cycle Count

PowerChoice Technology Manufacturer Default Power Condition Timer Values

Default Power Condition timer values have been established to ensure product reliability and data integrity. A minimum timer value threshold of two minutes ensures that the appropriate amount of background drive maintenance activities occur. Attempting to set a timer value less than the specified minimum timer value threshold results in an aborted EPC “Set Power Condition Timer” subcommand.

Seagate® PowerChoice™ Technology Provides Unprecedented Hard Drive Power Savings and Flexibility



Power Condition Name	Manufacturer Default Timer Values
Idle_A	2 min
Idle_B	4 min
Idle_C	10 min
Standby_Z	15 min

Setting power condition timer values less than the manufacturer specified defaults or issuing the EPC “Go to Power Condition” subcommand at a rate exceeding the default timers may limit this product’s reliability and data integrity.

For More Information

If you have additional questions on PowerChoice™ technology implementation, contact your Seagate technical representative.

Supported Extended Power Condition Feature Subcommands

EPC Subcommand	Description
00h	Restore Power Condition Settings
01h	Go to Power Condition
02h	Set Power Condition Timer
03h	Set Power Condition State

PowerChoice™ Technology-Supported Extended Power Condition Identifiers

Power Condition Identifiers	Power Condition Name
00h	Standby_Z
01..80h	Reserved
81h	Idle_A
82h	Idle_B
83h	Idle_C
84..FEh	Reserved
FFh	All EPC Power Conditions

AMERICAS Seagate Technology LLC 920 Disc Drive, Scotts Valley, California 95066, United States, +1 831 438 6550
 ASIA/PACIFIC Seagate Singapore International Headquarters Pte. Ltd. 7000 Ang Mo Kio Avenue 5, Singapore 569877, +65 6485 3888
 EUROPE, MIDDLE EAST AND AFRICA Seagate Technology SAS 16-18 rue de Dôme, 92100 Boulogne-Billancourt, France, +33 1 41 86 10 00

© 2010 Seagate Technology LLC. All rights reserved. Printed in USA. Seagate, Seagate Technology and the Wave logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. Barracuda, Cheetah, Constellation, PowerChoice, PowerTrim and Savvio are either trademarks or registered trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes; and one terabyte, or TB, equals one trillion bytes. Your computer operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Seagate reserves the right to change, without notice, product offerings or specifications. TP608.1-1003GB, March 2010