

LYVE™ Mobile Array



Data Sheet

Flexible Data Movement for Any Workflow



Seagate® Lyve™ Mobile Array is a portable, rackable data storage solution designed to quickly and securely store data at the edge or move data across your enterprise. Both the full-flash and hard drive versions enable universal data compatibility, versatile connectivity, secure encryption, and ruggedized data transportation. Lyve Mobile Array is available through Seagate's Lyve Mobile Services.



Best-Fit Applications

- Data migration to any major cloud and multicloud platform
- Large lift-and-shift data migration projects
- Disaster recovery and data redundancy transfer projects
- Edge data aggregation and quick data ingest to cloud, multicloud, or private data centers



Data activation at the edge.

Simple. Ready to use - Plug and play to fit any environment and data management workflow where you need it.

Efficient. Capture data anywhere and move it everywhere with a flexible and efficient subscription service model.

Secure. Seagate Secure™ offers industry-standard AES 256-bit hardware encryption at rest and in motion. Backed up by superior manufacturing, a global support, and service capabilities.

Scalable for multiple environments. Both office and data center ready, with RAID NVME, SSD and HDD configuration options available, and convenient desktop and data center connectivity.

Device management. Works seamlessly with Lyve Client software for superior security and RAID management as well as common DAS connections and high-performance network setups.

Flexible. Versatile interfaces including Thunderbolt™3, PCIe®, and USB-C let Lyve Mobile Array connect everywhere. Use the optional Lyve Mobile Rackmount Receivers for data center and 19" rack integration with Fibre Channel, iSCSI, and SAS ports.

Local high-performance storage applications with Seagate Lyve USM (High Performance PCIe gen 3.0) technology. PCIe read/write performance, up to 6GB/s and 12GB/s (dual port).



Specifications	
Physical Characteristics	Handle for carrying and racking Fully enclosed, non-serviceable
Capacity (6-bay array)	HDD Exos® SAS: 60TB, 96TB (6x HDD) SSD Nytro® SAS: 46TB, 92TB(6x SSD) NVMe Nytro®: 122TB (8x NVMe)
File System	exFAT (default) or user-defined
Interface (DAS)	2x USB-C for either Thunderbolt™ 3 (40Gb/s) or USB 3.2 (10Gb/s) 1x Lyve USM (High Performance PCIe® gen 3.0) Mobile Array PCIe Adapter required. SAS available with Rackmount Receiver option.
Network Interfaces (SAN)	Lyve™ Mobile Rackmount Receiver required for iSCSI (2xRJ45 1/10G copper 4x SFP+ 10/25G optical) or Fibre Channel (2x SFP+ 16/32G optical). SFP+ transceiver included with Rackmount Receiver
Throughput	Lyve USM (High Performance PCIe® gen 3.0): 6GB/s Lyve USM (High Performance PCIe® gen 3.0) Dual-Port: 12GB/s Thunderbolt 3: 2.8GB/s. USB 3.2 : 620MB/s
Supported RAID Modes	RAID 0 and RAID 5 (Default)
Noise Level	34dBA to 53dBA - Temperature and activity dependent
Nonoperating Drop Height	300mm/11.81in (HDD) 500mm/19.68in (SSD & NVMe)
Operating Drop Height	60mm/2.36in (HDD) 100mm/3.94in (SSD) 80mm/3.15in (NVMe)
Power Specifications (voltage)	LYVE MOBILE ARRAY: Power Input 100-240VAC, 50-60Hz using AC power supply Power Input 12VDC-15A using 12VDC power cord connecting to a 12VDC power source (battery) LYVE RACKMOUNT RECEIVER: Integrated redundant power supplies; Power Input 100-240VAC, 50-60Hz
Power Consumption (typical)	130W (typical), 240W max (during startup HDD version); 180W max (SSD version)
Environmental Compliance	REACH, RoHS-2
Safety and Regulatory	FCC, CE, RCM, VCCI, BSMI, NRTL, BIS, and KCC
Temperature (HDD model)	+5°C to +40°C +41°F to +104°F (operating) -40°C to +65°C -40°F to +149°F (nonoperating)
Temperature (SSD model)	+5°C to +50°C +41°F to +122°F (operating) -40°C to +65°C -40°F to +149°F (nonoperating)
Temperature (NVMe model)	+0°C to +50°C +32°F to +122°F (operating) -40°C to +65°C -40°F to +149°F (nonoperating)
Relative Humidity	10% to 60% (noncondensing, operating) 5% to 85% (noncondensing, nonoperating)
Vibration (max. operational)	SSD NVMe: 0.5G, Random, 5–500Hz (operating) HDD: 0.25G, Random, 5–500Hz (operating) SSD/NVMe + Mobile Mount + PCIe Adapter: meets transport vibration test standard IEC 60068-2-64
Vibration (max. nonoperating)	1.14G (HDD, SSD and NVMe nonoperating)
Security	Seagate Secure™ AES-256 bit encryption, crypto erase and TCG enterprise encryption
Software	Lyve™ Client software for setup, management, and security with physical product locking
Smart State Enabled	Pre-defined RGB LED states for various functions
Included Cables	Thunderbolt 3, external power supply
In-Transit Protection	Lyve Mobile Array Shipper
Lyve Mobile Array Shipper Tests	MIL-STD-810F §512.4, 514.5, 516.5; DEF STAN 81-41 Part 3/4 IP6X Category 2 and IPX7

Specifications		
	Product Dimensions	Box Dimensions
Height (in/mm)	5.7in 145mm	12.283in 312mm
Width (in/mm)	8.27in 210mm	19.882in 505mm
Depth (in/mm)	16.45in 418mm	25in 635mm
Weight (lb/kg) - NVMe	21.7lb 9.9kg	23.38kg 51.5lbs
Weight (lb/kg) - SSD	23lb 10.4kg	23.88kg 50.7lbs
Weight (lb/kg) - HDD	27.5lb 12.5kg	26.89kg 57.3lbs



Region	Model Number	Capacity	Notes
WW	STJX46000400	46TB	6 × 7.6TB Nytro SSD RAID 5 Capacity 38.4TB
WW	STJX60000400	60TB	6 × 10TB Exos HDD RAID 5 Capacity 50TB
WW	STJX90000400	92TB	6 × 15.3TB Nytro SSD RAID 5 Capacity 75TB
WW	STJX96000400	96TB	6 × 16TB Exos HDD RAID 5 Capacity 80TB
WW	STLN122000400	122TB	8 × 15.3TB Nytro NVMe SSD RAID 5 Capacity 106TB

Lyve Mobile Array Accessories	
Lyve Mobile Rackmount Receiver	Optional Lyve Rackmount Receiver required for use in standard 19-in rack. Functional with 1 or 2 Lyve Mobile Arrays
Rackmount Receiver Power	Integrated redundant power supplies; Power input 100–240vAC, 50–60Hz, max. 380W
Rackmount Receiver Ports	Version-dependent, field-replaceable interface cards.
Rackmount Receiver Dimension	4U (Height 7in/177.8mm Width 19in/482.6mm Depth 24.5in/624.84mm)
Lyve Mobile Mount (v1)	Fixture frame for edge or vehicle applications Product Dimensions: Height 7.76in/197mm Width 9.6in/244mm Depth 21.54in/547mm Weight: 11.7kg
Lyve Mobile Mount Front Loader (v2)	Lighter version of the Lyve Mobile Mount, with front horizontal loading of Lyve Mobile Array and front cable access. Product Dimensions (Door closed): Height 175mm Width 220mm Depth 549mm Weight: 5.6kg
Lyve Mobile PCIe Adapter	Provides NVMe-like storage over 2 SFF-8644 ports. Seamlessly integrates and recommended for use with Mobile Mount

Product Images			
Lyve Rackmount Receiver	Lyve Mobile Mount	Lyve Mobile PCIe Adapter	Lyve Mobile Array Shipper

System Requirements	What's Included
---------------------	-----------------

- Windows® 10 or higher
- MacOS® 10.15 or higher
- Ubuntu 20.04 and RedHat 8
- Lyve Client Software for Windows/macOS

- Seagate® Lyve™ Mobile Array
- Lyve Mobile Array Shipper
- Quick start guide
- Thunderbolt™ 3 active cable (1.5m)
- 20V power adapter for UK, EU/KR, USA/JP, AUS/NZ
- USB 3.1 gen2 cables (1m type C/C and 1m type C/A)

Lyve Mobile Array and Rackmount Receiver Options	Data Cable Included	Model Number
Lyve Mobile Mount (v1)		3EYAP1-RA1 STKU400
Lyve Mobile Mount Front Loader (v2)		3EYAP1-RA2 STKU400
Lyve Mobile PCIe Adapter		STKY400
Lyve Mobile Rackmount Receiver 2 Port SAS 12G (per Mobile Array)	HDSAS; length: 4m; 4pcs.	STKA400
Lyve Mobile Rackmount Receiver 2 Port Fibre Channel 16Gb (per Mobile Array)	UPC-FC/UPC Patch cord OM3; length: 2m; 4pcs.	STKA401
Lyve Mobile Rackmount Receiver 2 Port Fibre Channel 32Gb (per Mobile Array)	UPC-FC/UPC Patch cord OM3; length: 2m; 4pcs.	STKA402
Lyve Mobile Rackmount Receiver 2 Port RJ45 iSCSI 10GBASE-T (per Mobile Array)	CAT6A 26AWG 10G; length: 1.5m; 4pcs.	STKA403
Lyve Mobile Rackmount Receiver 4 Port iSCSI 25GB - 10G SFP+ (per Mobile Array)	UPC-FC/UPC Patch cord OM3; length: 2m; 8pcs.	STKA404
Lyve Mobile Rackmount Receiver 4 Port iSCSI 25GB - 25G SFP+ (per Mobile Array)	UPC-FC/UPC Patch cord OM3; length: 2m; 8pcs.	STKA405

seagate.com



© 2022 Seagate Technology LLC. All rights reserved. Seagate, Seagate Technology, and the Spiral logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. Exos, Lyve, the Lyve logo, Nytro, Seagate Secure, the Seagate Secure logo are either trademarks or registered trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. Thunderbolt and the Thunderbolt logo are trademarks of Intel Corporation in the U.S. and/or other countries. The PCIe word mark and/or PCIExpress design mark are registered trademarks and/or service marks of PCI-SIG. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Actual data rates may vary depending on operating environment and other factors, such as chosen interface and drive capacity. The export or re-export of Seagate hardware or software is regulated by the U.S. Department of Commerce, Bureau of Industry and Security (for more information, visit www.bis.doc.gov), and may be controlled for export, import, and use in other countries. Seagate reserves the right to change, without notice, product offerings or specifications. DS2044.7-2210US WW