

# Voyager 6 Plus SV0844D

## FEATURES

- Formatted Capacity 8.4 Gbytes
- 9.5 MSEC average seek time
- 5,400 rpm Spindle Speed
- EPR4 Read Channel with 16/17 rate code
- 200 Mbits/sec Maximum Data Rate
- Supports Ultra DMA 33/66 MB/s
- PIO Mode 4/Multi-Word DMA Mode 4/Ultra DMA
- Error Correction on the Fly (Multi-Burst)
- 512 KB Segmented Read/Write Cache Buffer
- S.M.A.R.T. compliant
- ATA-4 Host Protected Area Feature

## DRIVE ARCHITECTURE

Formatted Capacities	
Gbytes per Drive	8.4
Megabytes per Surface	2150
Bytes per Sector	512
Physical Organization	
Disks	2
Data Surfaces	4
Read/Write Heads	4
Cylinder	12,257
Sectors per Track	231 - 403

## FUNCTIONAL SPECIFICATIONS

Actuator Type	Rotary Voice Coil
Interface	Enhanced IDE
Servo	Embedded Sector Servo
Recording Method	16/17 EPR4
Recording Density (kbp, max.)	260
Flux Density (kfcpi, max.)	276
Track Density (tpi)	12,600

## PERFORMANCE SPECIFICATIONS

Seek Time (RD/WT typical)	
Track to Track	2.0/2.0 ms
Average	9.5/10.5 ms
Full Stroke	20/22 ms
Average Latency	5.56 ms
Spindle Speed	5,400 ± 0.1% rpm
Data Transfer Rate	
Media to/from Buffer	114 – 200 Mbits/s
Buffer to/from Host	16.6/33.3/66.6 MBytes/s
Start Time	
Typical	15 sec
Stop Time	
Typical	7 sec
Buffer Size	512 Kbytes

*Specifications are subject to change without notice*

## RELIABILITY SPECIFICATIONS

Recoverable Read Error	1 in 10 <sup>10</sup> bits
Non-recoverable Read Error	1 in 10 <sup>14</sup> bits
MTBF (POH)	500,000 hours
MTTR (typical)	5 minutes
Start/Stop Cycles	50,000
Component Design Life	5 years

## ENVIRONMENTAL SPECIFICATIONS

Temperature	
Operating	5 ~ 55 °C
Non-operating	-40 ~ 70 °C
Thermal Gradient (max.)	20 °C/15%/hr
Humidity (non-condensing)	
Operating	8 ~ 80 %
Non-operating	8 ~ 90 %
Maximum Wet Bulb	29/40 °C
Altitude (relative to sea level)	
Operating	-200 to 10,000 feet
Non-operating	-1,000 to 40,000 feet

## SHOCK AND VIBRATION

Linear Shock (1/2 sine pulse)		
Operating	11 ms	10 G
	(2 ms)	63 G
Non-operating	11 ms	75 G
	(2 ms)	200 G REF
Non-operating Rotational	2 ms	15,000 RAD/SEC <sup>2</sup>

Vibration (swept sine)		
Operating (1/2 octave per minute)		
5 ~ 21 Hz	0.034" (double amplitude)	
22 ~ 300 Hz	1.5 Gp-p	
300 ~ 500 Hz	.5 Gp-p	
Non-operating (1 octave per minute)		
5 ~ 21 Hz	0.195" (double amplitude)	
22 ~ 500 Hz	8 Gp-p	

## POWER CONSUMPTION

Power supply tolerance	+5V/±5%, 12V/±10%
Power Up Current (max.)	800/1550 MA
Read/Write (typical)	5.7 watts
Seek (30%) typical	6.4 watts
Idle (typical)	4.1 watts
Standby (typical)	1.3 watts
Sleep (typical)	1.3 watts

## ACOUSTIC NOISE

Sound Power	
Idle (Typical)	3.6 BEL
Random Read/Write (typical)	3.8 BEL

## PHYSICAL DIMENSION

Height	1 inch	Weight	1.3 pounds
Width	4 inches	Depth	5.75 inches

