

# Spinpoint™ M8U

## Mobile USB 3.0



Capacity		250GB	320GB	500GB	640GB	750GB	1TB	
Model	8 MB	HN-M250ABB	HN-M320ABB	HN-M500ABB	HN-M640ABB	HN-M750ABB	HN-M101ABB	Original Model Numbers
Model	8 MB	ST250LM003	ST320LM005	ST500LM014	ST640LM019	ST750LM023	ST1000LM025	New Model Numbers

### FEATURES

- Max. 500GB formatted capacity per disk
- TuMR/PMR head with FOD technology
- USB 3.0 Interface Support
- Load/Unload Head Technology
- SilentSeek™
- NoiseGuard™

### DRIVE CONFIGURATION

Capacity <sup>1</sup>	250 ~ 750GB, 1TB
Interface	USB 3.0
Buffer DRAM Size <sup>2</sup>	8 MB
Rotational Speed	5400 RPM Class

### PERFORMANCE SPECIFICATIONS

Average Seek time (typical)	12 ms
Average Latency	5.6 ms
Data Transfer Rate	
Media to/from Buffer (Max.)	145 MB/s
Buffer to/from Host (Max.)	400 MB/s
Drive Ready Time (typical) <sup>3</sup>	4 sec

### RELIABILITY SPECIFICATIONS

Non-recoverable Read Error	1 sector in 10 <sup>14</sup> bits
Controlled Ramp Load/Unload	600,000

### ACOUSTICS

Idle	2.4 Bel
Performance Seek	2.6 Bel

### POWER REQUIREMENTS

Voltage	+5V±5%
Spin-up Current (Max.)	750 mA
Seek (AVG) <sup>4</sup>	3.0 W
Read/Write (AVG)	3.2 W
Low Power Idle (AVG)	1.8 W
Standby (AVG)	1.4 W
Sleep (AVG)	1.4 W

### ENVIRONMENTAL SPECIFICATIONS

<b>Temperature</b>	
Operating	5 ~ 55 °C
Non-operating	-40 ~ 70 °C
<b>Humidity (non-condensing)</b>	
Operating	5-90 %
Non-operating	5-95 %
<b>Linear Shock (1/2 sine pulse)</b>	
Operating, 2ms	325 G
Non-operating, 2ms	750 G
<b>Vibration (swept sine, 1/4 octave per minute)</b>	
Operating	0.9 Grms
<b>Altitude (relative to sea level)</b>	
Operating	-300 to 3000 m
Non-operating	-400 to 15000 m

### PHYSICAL DIMENSION

Height	9.5 mm
Width	69.85 mm
Length	104 mm
Weight (max.)	107 g

\* Note : Design and specifications are subject to change without prior notice.

1 1MB = 1,000,000 Bytes, 1GB = 1,000,000,000 Bytes

Accessible capacity may vary as some OS uses binary numbering system for reported capacity

2 A small portion of the 8MB buffer memory is reserved for firmware use

3 Power-On to Drive Ready

4 30% duty cycle, random seek



2.5" HDD product specification Rev 2.1  
Match with product manual Rev 2.1

© 2012 Seagate Technology LLC. All rights reserved. Seagate and Seagate Technology are registered trademarks of Seagate Technology LLC in the United States and/or other countries. Momentus is either a trademark or registered trademark of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Actual data rates may vary depending on operating environment and other factors. The export or re-export of hardware or software containing encryption may be regulated by the U.S. Department of Commerce, Bureau of Industry and Security (for more information, visit [www.bis.doc.gov](http://www.bis.doc.gov)), and controlled for import and use outside of the U.S. Seagate reserves the right to change, without notice, product offerings or specifications.