

**PERFORMANCE****HIGHLIGHTS**

- 3.5-inch 7200 RPM performance hard drives
- Capacities up to 250GB
- Designed for performance PCs, PC gaming systems, and digital video

**FEATURES**

- Fast ATA/Enhanced IDE-compatible
- Ultra ATA data transfer speeds up to 133MB/sec
- Serial ATA option with transfer speeds up to 150MB/sec
- 100% FDB (fluid dynamic bearing) motors
- 2MB and 8MB cache buffers
- Shock Protection System™
- Data Protection System™

# DiamondMax® Plus 9

**ATA HARD DRIVE****60GB 80GB 120GB 160GB 200GB 250GB**

## Superior Performance Combined with Industry-leading Capacity

The DiamondMax® Plus 9 hard disk drive is designed to exceed previous standards for desktop performance. DiamondMax Plus 9 drives are offered with industry-standard capacity points up to 250GB. By delivering a performance hard drive using a highly leveraged design with state-of-the-art quality and reliability, Maxtor demonstrates technology leadership with DiamondMax Plus 9 drives.

### Maxtor-developed Ultra ATA interface and Serial ATA interface

The Maxtor-developed Ultra ATA interface has data transfer rates up to 133 MB/sec. DiamondMax Plus 9 drives will also be available with a serial ATA interface. With either Ultra ATA/133 or the increased speed and capabilities of Serial ATA/150, users will have a choice of the fastest data transfer rates and interface functionality available.

### Fluid Dynamic Bearing (FDB) Motors

All DiamondMax Plus 9 drives are equipped with FDB motors. This technology allows the drive to operate with very low sound output for performance users who are concerned about acoustics.

### Delivering Reliability

DiamondMax Plus 9 drives deliver high reliability and data integrity using the Maxtor-developed Shock Protection System (SPS) and Data Protection System (DPS). SPS and DPS give the drive enhanced protection against operating and non-operating shock to eliminate costly drive returns. When your application demands reliability, performance and capacity, DiamondMax Plus 9 drives are the ideal choice.



Capacity		60GB	80GB	120GB	160GB	200GB	250GB
Model	ATA/133 2MB buffer	6Y060L0	6Y080L0	6Y120L0	6Y160L0	—	—
	ATA/133 8MB buffer	—	6Y080P0	6Y120P0	6Y160P0	6Y200P0	6Y250P0
	SATA/150 8MB buffer	6Y060M0	6Y080M0	6Y120M0	6Y160M0	6Y200M0	6Y250M0

Note: L-FDB motor

### Performance Specifications

Rotational Speed	7200 RPM
Buffer Size	2MB and 8MB cache
External Transfer Rate(MB/sec)	ATA/133 133 SATA 150
Average Seek (ms)	≤9.3
Average Latency (ms)	4.2

### Disk Drive Configuration

Bytes per Sector/Block	512
Logical CHS	16,383/16/63

### Reliability Specifications

Start/Stop Cycles (min)	>50,000
Component Design Line (min)	5 years
Data Errors (non-recoverable)	<1 per 10E 15 bits read
Annualized Return Rate (ARR)	<1%

### Power Requirements

Mode	5V	12V
Seek (mA)	858	662
Idle (mA)	668	334
Standby (mA)	90	37

### Environmental Limits

#### Acoustics FDB motor

Idle (sound power: bel)	2.7
Seek (sound power: bel)	3.5

#### Temperature

Operating (°C)	5 to 55
Non-operating (°C)	-40 to 71

#### Shock

Operating Mechanical Shock 2ms (G)	60
Non-operating Mechanical Shock 2ms (G)	300

### Physical Dimensions

Width max (mm)	101.6
Length max (mm)	147
Height max (mm)	26.1
Weight max (LB/g)	1.27/630

SPS™

S · M · A · R · T  
S Y S T E M  
C O M P L I A N T

SERIAL  
ATA  
1.5Gb/s

ULTRA  
ATA/133

For support or information, call us at 1-800-2Maxtor or visit us at [www.maxtor.com](http://www.maxtor.com)

All Maxtor products are backed by our leading service and support staff.

Service includes:

- Advance replacement in 2 business days
- 24-hour on-line troubleshooting tools and e-mail
- Maxtor's commitment to total customer satisfaction
- Product support representatives available Monday-Friday

To speak with a Maxtor product support representative in the U.S. and Canada, call 1-800-2MAXTOR, Mon.-Fri. from 5 a.m. to 5 p.m. (PST).

In Europe, call +353 1 204 1111 Mon.-Thur. from 8:30 a.m. to 5 p.m. (GMT) and Fri. 8:30 a.m. to 4 p.m. (GMT).

In Australia, call +61 2 9369 3662. In Japan, call 00531653616, And in Singapore, call 65-6852-0220 or 1-800-481-6788.

Specifications subject to change without notice. GB means 1 billion bytes. Total accessible capacity varies depending on operating environment. Seek times and acoustics are average values.

©2003 Maxtor Corporation. Maxtor and DiamondMax are registered trademarks of Maxtor Corporation. All other trademarks are the property of their respective owner. Printed in the USA. Maxtor Corporation, 500 McCarthy Boulevard, Milpitas, CA, 95035. DS-DiamondMaxPlus9-8/04-CL.

**Maxtor**®

What drives you.™