

# Desktop HDD

Data Sheet

## The Power of One

- Seagate brings over 30 years of trusted performance and reliability to the Seagate® Desktop HDDs—now available in capacities up to 8TB
- Increase your capacity and drive down costs with up to 1.33TB-per-disk hard drive technology
- SATA 6Gb/s interface optimizes burst performance
- Seagate AcuTrac™ servo technology delivers dependable performance
- Free DiscWizard™ software enables high capacities on legacy PC BIOS systems
- Seagate Secure™ models provide hardware-based data security and deliver an Instant Secure Erase feature for safe, fast and easy drive retirement<sup>1</sup>
- Seagate Secure models meet the NIST 800-88 media sanitization specification and also support the Trusted Computer Group (TCG) Opal standard<sup>1</sup>

## Best-Fit Applications

- Desktop or all-in-one PCs
- Home servers
- Entry-level direct-attached storage devices (DAS)



<sup>1</sup> Seagate Secure models are not available in all countries. May require TCG-compliant host or controller support.



# Desktop HDD



Specifications	8TB	6TB	5TB	4TB	3TB
Standard Model Numbers <sup>1</sup>	ST8000DM002	ST6000DM001	ST5000DM002	ST4000DM000	ST3000DM001
Seagate Secure™ Model Numbers	—	—	—	—	ST3000DM002
Interface	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s
Cache	256MB	128MB	128MB	64MB	64MB
Model Name	Desktop HDD	Desktop HDD	Desktop HDD	Desktop HDD	formerly Barracuda
<b>Performance</b>					
SATA Transfer Rates Supported (Gb/s)	6.0/3.0/1.5	6.0/3.0/1.5	6.0/3.0/1.5	6.0/3.0/1.5	6.0/3.0/1.5
Max Sustainable Transfer Rate	220MB/s	220MB/s	220MB/s	180MB/s	210MB/s
<b>Configuration/Organization</b>					
Heads/Disks	6/12	6/12	6/12	8/4	6/3
Bytes per Sector	512E	512E	512E	512E	512E
<b>Voltage</b>					
Voltage Tolerance, Inc. Noise (5V)	±5%	±5%	±5%	±5%	±5%
Voltage Tolerance, Inc. Noise (12V)	±10%	±10%	±10%	±10%	±10%
<b>Reliability/Data Integrity</b>					
Contact Start/Stop Cycles	—	—	—	—	—
Load/Unload Cycles <sup>2</sup>	300,000	300,000	300,000	300,000	300,000
Nonrecoverable Read Errors per Bits Read, Max	1 per 10E14	1 per 10E14	1 per 10E14	1 per 10E14	1 per 10E14
Workload Rate Limit (TB/year)	55	55	55	55	55
Power-On Hours	2400	2400	2400	2400	2400
Warranty, Limited (years) <sup>3</sup>	2	2	2	2	2
<b>Power Management</b>					
Startup Power (12V, A)	2.0	2.0	2.0	2.0	2.5
Average Operating Power	9.0W	9.0W	9.0W	5.60W	8.0W
Idle Average (W)	7.2W	7.2W	7.2W	4.0W	5.40W
Standby/Sleep Mode	0.6W/0.6W	0.6W/0.6W	0.6W/0.6W	0.5W/0.5W	0.75W/0.75W
<b>Environmental/Temperature</b>					
Operating (ambient, min)	0°C	0°C	0°C	0°C	0°C
Operating (drive case, max)	60°C	60°C	60°C	60°C	60°C
Nonoperating (ambient, min)	-40°C	-40°C	-40°C	-40°C	-40°C
Nonoperating (ambient, max)	70°C	70°C	70°C	70°C	70°C
Halogen Free	Yes	Yes	Yes	Yes	Yes
RoHS Compliance	Yes	Yes	Yes	Yes	Yes
<b>Physical</b>					
Height (mm/in)	26.11mm/1.028in	26.11mm/1.028in	26.11mm/1.028in	26.11mm/1.028in	26.11mm/1.028in
Width (mm/in, max)	101.6mm/4.0in	101.6mm/4.0in	101.6mm/4.0in	101.6mm/4.0in	101.6mm/4.0in
Depth (mm/in, max)	146.99mm/5.787in	146.99mm/5.787in	146.99mm/5.787in	146.99mm/5.787in	146.99mm/5.787in
Weight (g/lb)	780g/1.72lb	780g/1.72lb	780g/1.72lb	610g/1.35lb	626g/1.38lb
Carton Unit Quantity	20	20	20	20	20
Cartons per Pallet / Cartons per Layer	40 / 8	40 / 8	40 / 8	40 / 8	40 / 8
<b>Special Features</b>					
Seagate AcuTrac™ Technology	Yes	Yes	Yes	Yes	Yes

<sup>1</sup> Seagate ships the 500GB, 320GB and 250GB models in both 4K- and 512-byte sectors. SmartAlign technology is included on 4K sector drives. Both drives are functionally and physically equivalent.

<sup>2</sup> Load/Unload tested to 600,000 cycles

<sup>3</sup> Extended warranty products available. Consult your distributor for details.

Specifications	2TB	1TB	500GB	320GB	250GB
Standard Model Numbers <sup>1</sup>	ST2000DM001	ST1000DM003	ST500DM002	ST320DM000	ST250DM000
Seagate Secure™ Model Numbers	ST2000DM002	ST1000DM004	—	—	—
Interface	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s
Cache	64MB	64MB	16MB	16MB	16MB
Model Name	formerly Barracuda	formerly Barracuda	formerly Barracuda	formerly Barracuda	formerly Barracuda
<b>Performance</b>					
SATA Transfer Rates Supported (Gb/s)	6.0/3.0/1.5	6.0/3.0/1.5	6.0/3.0/1.5	6.0/3.0/1.5	6.0/3.0/1.5
Max Sustainable Transfer Rate	210MB/s	210MB/s	144MB/s	144MB/s	144MB/s
<b>Configuration/Organization</b>					
Heads/Disks	4/2	2/1	2/1	2/1	1/1
Bytes per Sector	512E	512E	512E or 512	512E or 512	512E or 512
<b>Voltage</b>					
Voltage Tolerance, Inc. Noise (5V)	±5 %	±5 %	±5%	±5%	±5%
Voltage Tolerance, Inc. Noise (12V)	±10 %	±10 %	±10%	±10%	±10%
<b>Reliability/Data Integrity</b>					
Contact Start/Stop Cycles	—	50,000	50,000	50,000	50,000
Load/Unload Cycles <sup>2</sup>	300,000	300,000	—	—	—
Nonrecoverable Read Errors per Bits Read, Max	1 per 10E14	1 per 10E14	1 per 10E14	1 per 10E14	1 per 10E14
Workload Rate Limit (TB/year)	55	55	55	55	55
Power-On Hours	2400	2400	2400	2400	2400
Warranty, Limited (years) <sup>3</sup>	2	2	2	2	2
<b>Power Management</b>					
Startup Power (12V, A)	2.5	2.0	2.0	2.0	2.0
Average Operating Power	8.0W	5.3W	5.3W	6.2W	6.19W
Idle Average (W)	5.40W	4.60W	4.60W	4.60W	4.60W
Standby/Sleep Mode	0.75W/0.75W	0.94W/0.94W	0.94W/0.94W	0.79W/0.79W	0.79W/0.79W
<b>Environmental/Temperature</b>					
Operating (ambient, min)	0°C	0°C	0°C	0°C	0°C
Operating (drive case, max)	60°C	60°C	60°C	60°C	60°C
Nonoperating (ambient, min)	-40°C	-40°C	-40°C	-40°C	-40°C
Nonoperating (ambient, max)	70°C	70°C	70°C	70°C	70°C
Halogen Free	Yes	Yes	Yes	Yes	Yes
RoHS Compliance	Yes	Yes	Yes	Yes	Yes
<b>Physical</b>					
Height (mm/in)	26.11mm/1.028in	19.99mm/0.787in	19.99mm/0.787in	19.99mm/0.787in	19.99mm/0.787in
Width (mm/in, max)	101.6mm/4.0in	101.6mm/4.0in	101.6mm/4.0in	101.6mm/4.0in	101.6mm/4.0in
Depth (mm/in, max)	146.99mm/5.787in	146.99mm/5.787in	146.99mm/5.787in	146.99mm/5.787in	146.99mm/5.787in
Weight (g/lb)	626g/1.38lb	400g/0.88lb	415g/0.92lb	415g/0.92lb	415g/0.915lb
Carton Unit Quantity	20	25	25	25	25
Cartons per Pallet / Cartons per Layer	40 / 8	40 / 8	40 / 8	40 / 8	40 / 8
<b>Special Features</b>					
Seagate AcuTrac™ Technology	Yes	No	No	No	No

<sup>1</sup> Seagate ships the 500GB, 320GB and 250GB models in both 4K- and 512-byte sectors. SmartAlign technology is included on 4K sector drives. Both drives are functionally and physically equivalent.

<sup>2</sup> Load/Unload tested to 600,000 cycles

<sup>3</sup> Extended warranty products available. Consult your distributor for details.

SEAGATE.COM

AMERICAS Seagate Technology LLC 10200 South De Anza Boulevard, Cupertino, California 95014, United States, 408-658-1000

ASIA/PACIFIC Seagate Singapore International Headquarters Pte. Ltd. 7000 Ang Mo Kio Avenue 5, Singapore 569877, 65-6485-3888

EUROPE, MIDDLE EAST AND AFRICA Seagate Technology SAS 16-18, rue du Dôme, 92100 Boulogne-Billancourt, France, 33 1-4186 10 00

© 2015 Seagate Technology LLC. All rights reserved. Printed in USA. Seagate, Seagate Technology and the Spiral logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. AcuTrac, Barracuda, DiscWizard, Seagate Secure and SmartAlign are either trademarks or registered trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Actual data rates may vary depending on operating environment and other factors. The export or re-export of Seagate hardware or software is regulated by the U.S. Department of Commerce, Bureau of Industry and Security (for more information, visit [www.bis.doc.gov](http://www.bis.doc.gov)), and may be controlled for export, import and use in other countries. Seagate reserves the right to change, without notice, product offerings or specifications. DS1770.7-1511US November 2015