

Desktop HDD

Data Sheet

The Power of One

- Seagate brings over 30 years of trusted performance and reliability to the Seagate® Desktop HDDs—now available in capacities up to 8 TB
- Increase your capacity and drive down costs with up to 1.33TB-per-disk hard drive technology
- SATA 6Gb/s interface optimises burst performance.
- Seagate AcuTrac™ servo technology delivers dependable performance
- Free DiscWizard™ software enables high capacities on legacy PC BIOS systems
- Seagate Secure™ models provide hardware-based data security and deliver an Instant Secure Erase feature for safe, fast and easy drive retirement¹
- Seagate Secure models meet the NIST 800-88 media sanitization specification and also support the Trusted Computer Group (TCG) Opal standard¹



Best-Fit Applications

- Desktop or all-in-one PCs
- Home servers
- Entry-level direct-attached storage devices (DAS)

¹ Seagate Secure models are not available in all countries. May require TCG-compliant host or controller support.



Desktop HDD



Specifications	8TB	6TB	5TB	4TB	3TB
Standard Model Numbers ¹	ST8000DM002	ST6000DM001	ST5000DM002	ST4000DM000	ST3000DM001
Seagate Secure™ Model Numbers	—	—	—	—	ST3000DM002
Interface	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s
Cache	256 MB	128 MB	128 MB	64 MB	64 MB
Model Name	Desktop HDD	Desktop HDD	Desktop HDD	Desktop HDD	formerly Barracuda
Performance					
SATA Transfer Rates Supported (Gb/s)	6.0/3.0/1.5	6.0/3.0/1.5	6.0/3.0/1.5	6.0/3.0/1.5	6.0/3.0/1.5
Max Sustainable Transfer Rate	220MB/s	220MB/s	220MB/s	180MB/s	210MB/s
Configuration/Organisation					
Heads/Discs	6/12	6/12	6/12	8/4	6/3
Bytes per Sector	512E	512E	512E	512E	512E
Voltage					
Voltage Tolerance, Inc. Noise (5V)	±5%	±5%	±5%	±5%	±5%
Voltage Tolerance, Inc. Noise (12V)	±10%	±10%	±10%	±10%	±10%
Reliability/Data Integrity					
Contact Start/Stop Cycles ²	—	—	—	—	—
Load/Unload Cycles ³	300,000	300,000	300,000	300,000	300,000
Non-recoverable Read Errors per Bits Read, Max	1 per 10E14	1 per 10E14	1 per 10E14	1 per 10E14	1 per 10E14
Workload Rate Limit (TB/year)	55	55	55	55	55
Power-on Hours	2,400	2,400	2,400	2,400	2,400
Warranty, Limited (years) ⁴	2	2	2	2	2
Power Management					
Startup Power (12V, A)	2	2	2	2	2.5
Average Operating Power	9 W	9 W	9 W	5.6 W	8 W
Idling Average (W)	7.2 W	7.2 W	7.2 W	4 W	5.4 W
Standby/Sleep Mode (,)	0.6 W/0.6 W	0.6 W/0.6 W	0.6 W/0.6 W	0.5 W/0.5 W	0.75 W/0.75 W
Environmental/Temperature					
Operating (ambient, min)	0°C	0°C	0°C	0°C	0°C
Operating (drive case, max)	60°C	60°C	60°C	60°C	60°C
Non-operating (ambient, min)	-40°C	-40°C	-40°C	-40°C	-40°C
Non-operating (ambient, max)	70°C	70°C	70°C	70°C	70°C
Halogen-free	Yes	Yes	Yes	Yes	Yes
RoHS compliance	Yes	Yes	Yes	Yes	Yes
Physical					
Height (mm/in)	26.11 mm/1.028 in	26.11 mm/1.028 in	26.11 mm/1.028 in	26.11 mm/1.028 in	26.11 mm/1.028 in
Width (mm/in, max)	101.6 mm/4 in	101.6 mm/4 in	101.6 mm/4 in	101.6 mm/4 in	101.6 mm/4 in
Depth (mm/in, max)	146.99 mm/5.787 in	146.99 mm/5.787 in	146.99 mm/5.787 in	146.99 mm/5.787 in	146.99 mm/5.787 in
Weight (lb/g)	780 g/1.72 lb	780 g/1.72 lb	780 g/1.72 lb	610 g/1.35 lb	626 g/1.38 lb
Carton Unit Quantity	20	20	20	20	20
Cartons per Pallet / Cartons per Layer	40 / 8	40 / 8	40 / 8	40 / 8	40 / 8
Special Features					
Seagate AcuTrac™ Technology	Yes	Yes	Yes	Yes	Yes

¹ Seagate ships the 500GB, 320GB and 250GB models in both 4K- and 512-byte sectors. SmartAlign technology is included on 4K sector drives. Both drives are functionally and physically equivalent.

² At 25°C and 50% relative humidity.

³ Load/Unload tested to 600,000 cycles.

⁴ Extended warranty products available. Consult your distributor for details.



Desktop HDD



Specifications	2TB	1TB	500GB	320GB	250GB
Standard Model Numbers ¹	ST2000DM001	ST1000DM003	ST500DM002	ST320DM000	ST250DM000
Seagate Secure™ Model Numbers	ST2000DM002	ST1000DM004	—	—	—
Interface	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s
Cache	64 MB	64/32 MB	16 MB	16 MB	16 MB
Model Name	formerly Barracuda	formerly Barracuda	formerly Barracuda	formerly Barracuda	formerly Barracuda
Performance					
SATA Transfer Rates Supported (Gb/s)	6.0/3.0/1.5	6.0/3.0/1.5	6.0/3.0/1.5	6.0/3.0/1.5	6.0/3.0/1.5
Max Sustainable Transfer Rate	210MB/s	210MB/s	144MB/s	144MB/s	144MB/s
Configuration/Organisation					
Heads/Discs	6/3 or 4/2	2/1	2/1	2/1	1/1
Bytes per Sector	512E	512E	512E or 512	512E or 512	512E or 512
Voltage					
Voltage Tolerance, Inc. Noise (5V)	±5 %	±5%	±5%	±5%	±5%
Voltage Tolerance, Inc. Noise (12V)	±10 %	±10%	±10%	±10%	±10%
Reliability/Data Integrity					
Contact Start/Stop Cycles ²	—	50,000	50,000	50,000	50,000
Load/Unload Cycles ³	300,000	300,000	—	—	—
Non-recoverable Read Errors per Bits Read, Max	1 per 10E14	1 per 10E14	1 per 10E14	1 per 10E14	1 per 10E14
Workload Rate Limit (TB/year)	55	55	55	55	55
Power-on Hours	2,400	2,400	2,400	2,400	2,400
Warranty, Limited (years) ⁴	2	2	2	2	2
Power Management					
Startup Power (12V, A)	2.5	2	2	2	2
Average Operating Power	8 W	5.3 W	6.19 W	6.2 W	6.19 W
Idling Average (W)	5.4 W	4.6 W	4.6 W	4.6 W	4.6 W
Standby/Sleep Mode (,)	0.75 W/0.75 W	0.94 W/0.94 W	0.79 W/0.79 W	0.79 W/0.79 W	0.79 W/0.79 W
Environmental/Temperature					
Operating (ambient, min)	0°C	0°C	0°C	0°C	0°C
Operating (drive case, max)	60°C	60°C	60°C	60°C	60°C
Non-operating (ambient, min)	-40°C	-40°C	-40°C	-40°C	-40°C
Non-operating (ambient, max)	70°C	70°C	70°C	70°C	70°C
Halogen-free	Yes	Yes	Yes	Yes	Yes
RoHS compliance	Yes	Yes	Yes	Yes	Yes
Physical					
Height (mm/in)	26.11 mm/1.028 in	19.99 mm/0.787 in	19.99 mm/0.787 in	19.99 mm/0.787 in	19.99 mm/0.787 in
Width (mm/in, max)	101.6 mm/4 in	101.6 mm/4 in	101.6 mm/4 in	101.6 mm/4 in	101.6 mm/4 in
Depth (mm/in, max)	146.99 mm/5.787 in	146.99 mm/5.787 in	146.99 mm/5.787 in	146.99 mm/5.787 in	146.99 mm/5.787 in
Weight (lb/g)	626 g/1.38 lb	400 g/0.88 lb	415 g/0.915 lb	415 g/0.915 lb	415 g/0.915 lb
Carton Unit Quantity	20	25	25	25	25
Cartons per Pallet / Cartons per Layer	40 / 8	40 / 8	40 / 8	40 / 8	40 / 8
Special Features					
Seagate AcuTrac™ Technology	Yes	No	No	No	No

¹ Seagate ships the 500GB, 320GB and 250GB models in both 4K- and 512-byte sectors. SmartAlign technology is included on 4K sector drives. Both drives are functionally and physically equivalent.

² At 25°C and 50% relative humidity.

³ Load/Unload tested to 600,000 cycles.

⁴ Extended warranty products available. Consult your distributor for details.

SEAGATE.COM

AMERICAS Seagate Technology LLC 10200 South De Anza Boulevard, Cupertino, California 95014, United States, 408-658-1000

ASIA/PACIFIC Seagate Singapore International Headquarters Pte. Ltd. 7000 Ang Mo Kio Avenue 5, Singapore 569877, 65-6485-3888

EUROPE, MIDDLE EAST AND AFRICA Seagate Technology SAS 16-18, rue du Dôme, 92100 Boulogne-Billancourt, France, 33 1-4186 10 00

© 2016 Seagate Technology LLC. All rights reserved. Printed in USA. Seagate, Seagate Technology and the Spiral logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. AcuTrac, Barracuda, DiscWizard, Seagate Secure and SmartAlign are either trademarks or registered trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes; and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Actual data rates may vary depending on operating environment and other factors. The export or re-export of Seagate hardware or software is regulated by the U.S. Department of Commerce, Bureau of Industry and Security (for more information, visit www.bis.doc.gov), and may be controlled for export, import and use in other countries. Seagate reserves the right to change, without notice, product offerings or specifications. DS1770.9-1603UK March 2016