



DATA SHEET

Trusted. Efficient. Versatile.

Exos 5E8

The Seagate[®] Exos[™] 5E8 hard drives are the most affordable enterprise-class drives designed specifically for active-archive applications in cloud storage, cold storage and online data archiving. Exos 5E8 provides power-efficient, high-density storage for 24×7 data centre operations.





Key Features and Benefits

- High capacity, energy efficiency and lowest TCO
- Over 30 years of trusted reliability for online long-term storage
- Engineered for 24×7 workloads of 180 TB per year
- Drive down costs with up to 2 TBper-disk hard drive technology
- SATA 6 Gb/s interface optimises burst performance.
- AcuTrac[®] servo technology for dependable performance
- Free Seagate DiscWizard[™] software

Best-Fit Applications²

- Cost-effective online archiving
- Object storage
- Big Data cold storage
- Cloud active archive
- Low random-write workloads

Reliable Active-Archive Enterprise Hard Drive

Exos 5E8 hard drives support up to 8 TB per drive¹ and offer affordable cold storage for data centre infrastructures requiring a highly reliable enterprise hard drive. The Exos 5E8 hard drive helps to catalyse the datasphere, enabling data centre architects and IT professionals to deliver trusted performance, rock-solid reliability and ironclad security.

Exos 5E8 is designed to best perform when write workloads are primarily sequential in nature. For more random write workloads, we recommend Exos 7E8.

Store More Data at Lower Costs

The Exos 5E8 hard drives are backed by an 800,000 hour MTBF and support workloads of 180 TB per year. The Exos 5E8 offers a low cost/TB online data archive solution with a SATA 6 Gb/s interface that optimises burst performance, and on-demand, time-to-ready PowerChoice™ technology to help ensure low power consumption.

Efficiently Lower Your TCO

Exos 5E8 ensures archival data confidence with a reliable, low-power data retrieval based on Shingled Magnetic Recording (SMR) technology for efficient cold storage operations even in harsh data centre environments. The Exos 5E8 serves up impressive sequential throughput and is intended for use in large-scale data centres where density, power consumption, data integrity and data retrieval are paramount.

Enhanced Enterprise Reliability, Data Protection and Security

Exos 5E8 drives deliver exceptional security to help protect data where it lives — on the drive. Exos 5E8 safeguards firmware with Secure Downloads & Diagnostics.

1 Seagate recommends validating your configuration with your HBA/RAID controller manufacturer to ensure full capacity capabilities.

 $2 \ \mathsf{Exos} \ \mathsf{5E8} \ \mathsf{hard} \ \mathsf{drives} \ \mathsf{are} \ \mathsf{not} \ \mathsf{intended} \ \mathsf{for} \ \mathsf{surveillance} \ \mathsf{or} \ \mathsf{NAS} \ \mathsf{applications}, \ \mathsf{and} \ \mathsf{you} \ \mathsf{may} \ \mathsf{experience} \ \mathsf{lower} \ \mathsf{performance} \ \mathsf{in} \ \mathsf{these} \ \mathsf{environments}.$

For these applications, Seagate IronWolf TM and Seagate SkyHawk TM hard drives are suggested for better performance and reliability.





Specifications	8TB
Model Number	ST8000AS0003
Interface	SATA 6Gb/s
Performance	
Cache, Multi-segmented (MB)	256
SATA Transfer Rates Supported (Gb/s)	6.0/3.0/1.5
Max. Sustained Transfer Rate OD (MB/s)	190MB/s
Configuration/Organisation	
Heads/Discs	8/4
Bytes per Sector	512e
SMR Technology, Drive-Managed	Yes
Rotational Vibration (RV) Sensor	Yes
Voltage	
Voltage Tolerance, Inc. Noise (5 V)	±5%
Voltage Tolerance, Inc. Noise (12 V)	±10%
Reliability/Data Integrity	
Load/Unload Cycles	300,000
Non-recoverable Read Errors per Bits Read, Max	1 per 10E14
Workload Rate Limit (TB/Year)	180
Power-On Hours per Year (24×7)	8,760
MTBF	800,000 hr
Warranty, Limited (years)	3
Power Consumption	
Startup Power (A)	2
Operating Mode, Typical (W)	5.3
Idle Average (W) ²	3.7
Standby Mode (W)	<1.0
Sleep Mode (W)	<1.0
Environmental	
Operating (ambient, min °C)	0
Operating Temperature (drive case max °C)	60
Non-operating Temperature (ambient °C)	-40 – 70
Low Halogen	Yes
RoHS compliance	Yes
Physical	
Height (mm/in)	26.11 mm/1.028 in
Width (mm/in)	101.6 mm/4 in
Depth (mm/in, max)	146.99 mm/5.787 in
Weight (lb/g)	605 g/1.334 lb
Carton Unit Quantity	20
Cartons per Pallet / Cartons per Layer	40/8

¹ Extended warranty products available. Consult your distributor for details.

² During periods of drive idle, some offline activity may occur according to the S.M.A.R.T. specification, which may increase acoustic and power to operational levels. Consult the product manual for more information.

seagate.com



AMERICAS Seagate Technology LLC 10200 South De Anza Boulevard, Cupertino, California 95014, United States, 408-658-1000
ASIA/PACIFIC Seagate Singapore International Headquarters Pte. Ltd. 7000 Ang Mo Kio Avenue 5, Singapore 569877, 65-6485-3888
EUROPE, MIDDLE EAST AND AFRICA Seagate Technology SAS 16-18, rue du Dôme, 92100 Boulogne-Billancourt, France, 33 1-4186 10 00

© 2017 Seagate Technology LLC. All rights reserved. Seagate, Seagate Technology and the Spiral logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. AcuTrac, DiscWizard, Exos, the Exos logo, IronWolf, PowerChoice and SkyHawk are either trademarks or registered trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes; and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Actual data rates may vary depending on operating environment and other factors, such as chosen interface and disk capacity. Seagate reserves the right to change, without notice, product offerings or specifications. DS1954.2-1712GB December 2017