



DATA SHEET—SEAGATE CONFIDENTIAL

Scalable. Responsive. Innovative.
Exos X18



Seagate manufactures hard drives that specifically address the demand for hyperscale cloud scalability. As the flagship of the Seagate® X class, the Exos® X18 enterprise hard drives are the highest-capacity hard drives in the fleet.



Maximum Storage Capacity for Highest Rack Space Efficiency

Market-leading 18TB HDD offering the highest capacity available for more petabytes per rack¹

Highly reliable performance with enhanced caching, making it the logical choice for cloud data center and massive scale-out data center applications

Hyperscale SATA model tuned for large data transfers and low latency

PowerBalance™ feature optimizes Watts/TB

Maximize total cost of ownership savings through lower power and weight with helium sealed-drive design

Proven helium side-sealing weld technology for added handling robustness and leak protection

Digital environmental sensors to monitor internal drive conditions for optimal operation and performance

Data protection and security— Seagate Secure™ features for safe, affordable, fast, and easy drive retirement

Proven enterprise-class reliability backed by **5-year limited warranty and 2.5M-hr MTBF rating**

Best-Fit Applications

- Scalable hyperscale applications/cloud data centers
- Massive scale-out data centers
- Big data applications
- High-capacity density RAID storage
- Mainstream enterprise external storage arrays
- Distributed file systems, including Hadoop and Ceph
- Enterprise backup and restore—D2D, virtual tape
- Centralized surveillance

¹ Compared to 14TB competitive product



Specifications	SATA 6Gb/s
Capacity	18TB
SED Model (512e) ¹	ST18000NM001J
Features	
Helium Sealed-Drive Design	Yes
Conventional Magnetic Recording (CMR)	Yes
SuperParity	Yes
Low Halogen	Yes
PowerChoice™ Idle Power Technology	Yes
PowerBalance™ Power/Performance Technology	Yes
Hot-Plug Support ²	Yes
Cache, Multisegmented (MB)	256
Organic Solderability Preservative	Yes
RSA 3072 Firmware Verification (SD&D)	Yes
Reliability/Data Integrity	
Mean Time Between Failures (MTBF, hours)	2,500,000
Reliability Rating @ Full 24x7 Operation (AFR)	0.35%
Nonrecoverable Read Errors per Bits Read	1 sector per 10E15
Power-On Hours per Year (24x7)	8760
512e Sector Size (Bytes per Sector)	512
Limited Warranty (years)	5
Performance	
Spindle Speed (RPM)	7200RPM
Interface Access Speed (Gb/s)	6.0, 3.0
Max. Sustained Transfer Rate OD (MB/s, MiB/s)	270/258
Random Read/Write 4K QD16 WCD (IOPS)	170/310
Average Latency (ms)	4.16
Interface Ports	Single
Rotation Vibration @ 20-1500 Hz (rad/sec ²)	12.5
Power Consumption	
Idle A (W) Average	5.3W
Max Operating, Random Read/Write 4K/16Q (W)	9.4, 7.7
Power Supply Requirements	+12 V and +5 V
Environmental	
Temperature, Operating (°C)	5°C – 60°C
Vibration, Nonoperating: 2 to 500Hz (Grms)	2.27
Shock, Operating 2ms (Read/Write) (Gs)	50
Shock, Nonoperating 2ms (Gs)	200
Physical	
Height (mm/in, max) ³	26.1mm/1.028in
Width (mm/in, max) ³	101.85mm/4.010in
Depth (mm/in, max) ³	147.0mm/5.787in
Weight (g/lb)	670g/1.477lb
Carton Unit Quantity	20
Cartons per Pallet/Cartons per Layer	40/8

¹ Self-Encrypting Drives (SED) available through franchised authorized distributors. May require TCG-compliant host or controller support.

² Supports Hotplug operation per Serial ATA Revision 3.3 specification

³ These base deck dimensions conform to the Small Form Factor Standard (SFF-8301) found at www.sffcommittee.org. For connector-related dimensions, see SFF-8323.

© 2020 Seagate Technology LLC. All rights reserved. Seagate, Seagate Technology, and the Spiral logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. Exos, the Exos logo, PowerBalance, PowerChoice, and Seagate Secure are either trademarks or registered trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Actual data rates may vary depending on operating environment and other factors, such as chosen interface and disk capacity. The export or re-export of Seagate hardware or software is regulated by the U.S. Department of Commerce, Bureau of Industry and Security (for more information, visit www.bis.doc.gov), and may be controlled for export, import, and use in other countries. Seagate reserves the right to change, without notice, product offerings or specifications. DS2045.1N-2007US July 2020