



DATA SHEET

Uncompromised Endurance. Unparalleled Performance.

IronWolf Pro 125 SSD



NAS-optimized Seagate® IronWolf® Pro 125 SSDs—offering blistering performance, power loss data protection, and multi-user workload support capable of 1 DWPD.



Best-Fit Applications

- Ultra high endurance NAS
- All-flash array and desktop NAS
- Creative pro, SMB, and SME
- Media server
- SSD cache in enabled NAS



Key Advantages

High Endurance: 1 DWPD delivers endurance and performance, offering the ideal SSD solution for 24x7, multi-user NAS environments

Power Loss Data Protection: Enjoy peace of mind during a power loss knowing your data can stay safe

IronWolf Health Management: Embedded software monitors your SSD NAS drive health in compatible NAS, notifying you to intervene before a catastrophic event occurs

Data Recovery: Rest easy with three years of Rescue Data Recovery Services, offering an industry-leading 95% success rate against unexpected data loss from power outages, natural disasters, user error, viruses, and more

Wide Range of Capacity Options: Choose from an extensive portfolio of capacities, including 240GB, 480GB, 960GB, 1.92TB, and 3.84TB

Warranty: Enjoy long-term peace of mind with the included five-year limited warranty protection plan and three-year Rescue Services



Specifications					
Capacity	3.84TB	1.92TB	960GB	480GB	240GB
Standard Model	ZA3840NX10001	ZA1920NX10001	ZA960NX10001	ZA480NX10001	ZA240NX10001
Features					
Interface	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s
NAND Flash Type	3D TLC	3D TLC	3D TLC	3D TLC	3D TLC
Form Factor	2.5 in × 7mm	2.5 in × 7mm	2.5 in × 7mm	2.5 in × 7mm	2.5 in × 7mm
Performance					
Sequential Read (MB/s) Sustained, 128KB QD32 ¹	545	545	545	545	545
Sequential Write (MB/s) Sustained, 128KB QD32 ¹	520	520	520	500	360
Random Read (IOPS) Sustained, 4KB QD32 ¹	96,000	96,000	96,000	96,000	90,000
Random Write (IOPS) Sustained, 4KB QD32 ¹	30,000	30,000	25,000	16,000	12,000
Endurance/Reliability					
Total Bytes Written (TB)	7000	3500	1750	875	435
Nonrecoverable Read Errors per Bits Read	1 per 10E17	1 per 10E17	1 per 10E17	1 per 10E17	1 per 10E17
Mean Time Between Failures (MTBF, hours)	2,000,000	2,000,000	2,000,000	2,000,000	2,000,000
Rescue Data Recovery Services ²	Yes	Yes	Yes	Yes	Yes
Warranty, Limited (years)	5	5	5	5	5
Power Management					
Power Supply	5V	5V	5V	5V	5V
+5V Active Max Average Power (W)	5.0	4.4	4.0	3.0	2.5
Max Average Idle Power (W)	1.9	1.8	1.6	1.4	1.4
Environmental					
Temperature, Operating Internal (°C)	0 to 70	0 to 70	0 to 70	0 to 70	0 to 70
Temperature, Nonoperating (°C)	-40 to 85	-40 to 85	-40 to 85	-40 to 85	-40 to 85
Shock, Nonoperating: 0.5ms (Gs)	1500	1500	1500	1500	1500
Physical					
Height (in/mm, max)	0.279in/7.10mm	0.279in/7.10mm	0.279in/7.10mm	0.279in/7.10mm	0.279in/7.10mm
Width (in/mm, max)	2.760in/70.10mm	2.760in/70.10mm	2.760in/70.10mm	2.760in/70.10mm	2.760in/70.10mm
Depth (in/mm, max)	3.950in/100.35mm	3.950in/100.35mm	3.950in/100.35mm	3.950in/100.35mm	3.950in/100.35mm
Weight (lb/g)	0.136lb/62g	0.132lb/60g	0.130lb/59g	0.123lb/56g	0.121lb/55g

¹ Performance data is based on testing under certain workload conditions and is subject to change.

² Three-year Rescue Data Recovery Services not available in all countries. Contact your Seagate sales representative for further details.



Ordering Information	
Specifications	
Retail Packaging	Box Dimensions
Depth/Length (in/mm)	0.95in/24mm
Width (in/mm)	4.3in/109mm
Height (in/mm)	6.11in/155mm
Weight (lb/kg)	0.38lb/0.17kg
Master Carton Dimensions	
Depth/Length (in/mm)	6.03in/153mm
Width (in/mm)	11.5in/292mm
Height (in/mm)	5.6in/140mm
Weight (lb/kg)	4.2lb/1.9kg
Pallet Dimensions	
Depth/Length (in/mm)	48in/1219mm
Width (in/mm)	20in/508mm
Height (in/mm)	28in/706mm
Weight (lb/kg)	148lb/67.28
Quantities	
Boxes per Master Carton	10
Master Cartons per Pallet	48
Pallet Layers	4

System Requirements	What's Included
---------------------	-----------------

- SATA 6Gb/s or SATA 3Gb/s port
- Windows[®] 10, Windows 8.1
- Linux
- Seagate[®] IronWolf[®] Pro 125 SSD

Region	Model Number	Capacity	Limited Warranty (years)	UPC Code	EAN Code	Multi-Pack UPC
WW	ZA3840NX1A001	3.84TB	5	763649146989	8719706027250	10763649146986
WW	ZA1920NX1A001	1.92TB	5	763649146972	8719706027243	10763649146979
WW	ZA960NX1A001	960GB	5	763649146965	8719706027236	10763649146962
WW	ZA480NX1A001	480GB	5	763649146958	8719706027229	10763649146955
WW	ZA240NX1A001	240GB	5	763649146941	8719706027212	10763649146948

seagate.com



© 2020 Seagate Technology LLC. All rights reserved. Seagate, Seagate Technology, and the Spiral Logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. IronWolf and the IronWolf logo are either trademarks or registered trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Actual data rates may vary depending on operating environment and other factors, such as chosen interface and disk capacity. Seagate reserves the right to change, without notice, product offerings or specifications. DS2053.2-2011US November 2020