



3.5 HARD DRIVE DATA SHEET

Smart. Safe. Secure.
Surveillance-Optimized Storage



Seagate® SkyHawk™ AI is the world's first, purpose-built drive for artificial intelligence (AI)-enabled surveillance solutions.



Best-Fit Applications

- Network video recorders (NVR)
- AI-enabled NVR systems



SKYHAWK
HEALTH

Key Advantages

ImagePerfect™ AI firmware for superior image integrity alongside additional AI workload support in always-on, AI-enabled surveillance systems.

Custom designed to support an additional 32 AI streams while simultaneously and flawlessly recording footage up to 64 HD cameras.

Designed and built to handle heavy surveillance workloads in traditional video recording and advanced video analytics environments. At 550TB/year, SkyHawk AI is designed for 3× the workload of standard surveillance drives.

Advanced vibration management for superior and sustained performance in 16+ bay NVR systems.

SkyHawk Health Management actively helps protect your surveillance storage by focusing on prevention, intervention, and recovery options.¹ Included is RAID RapidRebuild™, which provides 3× faster volume rebuilds.

Improved reliability and reduced total cost of ownership with 1.5M-hr. MTBF and 3-year limited warranty.

Unparalleled data protection with an optional 2-year Rescue Data Recovery Services plan, providing access to Seagate's secure labs with industry-leading data recovery success rates.

¹ Contact your Seagate sales representative for further information.



Specifications	14TB	12TB	10TB	10TB	8TB
Capacity	14TB	12TB	10TB	10TB	8TB
Standard Model Numbers	ST14000VE0008	ST12000VE0008	ST10000VE0008	ST10000VE0004	ST8000VE0004
Interface	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s
Features and Performance					
Drive Bays Supported	16+	16+	16+	16+	16+
AI Streams ¹	32	32	32	32	32
HD Cameras Supported	Up to 64	Up to 64	Up to 64	Up to 64	Up to 64
RV Sensors	Yes	Yes	Yes	Yes	Yes
Max. Sustained Transfer Rate OD (MB/s)	250MB/s	250MB/s	250MB/s	235MB/s	235MB/s
Cache (MB)	256	256	256	256	256
Reliability/Data Integrity					
Tarnish Resistant	Yes	Yes	Yes	Yes	Yes
Load/Unload Cycles	300,000	300,000	300,000	300,000	300,000
Nonrecoverable Read Errors per Bits Read, Max	1 per 10E15	1 per 10E15	1 per 10E15	1 per 10E15	1 per 10E15
Power-On Hours per Year (24x7)	8760	8760	8760	8760	8760
Workload Rate Limit (WRL) ²	550	550	550	550	550
MTBF	1,500,000hr	1,500,000hr	1,500,000hr	1,500,000hr	1,500,000hr
Warranty, Limited (years) ³	3	3	3	3	3
Power Management					
Startup Current, Typical (12V, A)	1.8	1.8	1.8	1.8	1.8
Average Operating Power (W)	6.9W	6.9W	6.9W	7.2W	7.2W
Idle Average (W)	4.9W	4.9W	4.9W	4.9W	4.9W
Standby Mode/Sleep Mode, Typical (W)	1.2/1.2	1.2/1.2	1.2/1.2	0.8/0.8	0.8/0.8
Voltage Tolerance (5V)	±5%	±5%	±5%	±5%	±5%
Voltage Tolerance (12V)	±10%	±10%	±10%	±10%	±10%
Environmental/Temperature					
Operating (ambient, min °C)	5	5	5	5	5
Operating (drive case, max °C) ⁴	70	70	70	70	70
Nonoperating (ambient, min °C)	-40	-40	-40	-40	-40
Physical					
Height (mm/in, max)	26.11mm/1.028in	26.11mm/1.028in	26.11mm/1.028in	26.11mm/1.028in	26.11mm/1.028in
Width (mm/in, max)	101.85mm/4.01in	101.85mm/4.01in	101.85mm/4.01in	101.85mm/4.01in	101.85mm/4.01in
Depth (mm/in, max)	146.99mm/5.787in	146.99mm/5.787in	146.99mm/5.787in	146.99mm/5.787in	146.99mm/5.787in
Weight (g/lb)	690g/1.521lb	690g/1.521lb	690g/1.521lb	650g/1.433lb	650g/1.433lb
Carton Unit Quantity	20	20	20	20	20
Cartons per Pallet/Cartons per Layer	40/8	40/8	40/8	40/8	40/8

¹ 32 AI streams = 16 AI channels.

² SkyHawk AI surveillance drives are designed for always-on workloads of 550TB/year. For higher transaction workloads, see Seagate's enterprise-class drive offerings.

³ Extended warranty options available. Consult your distributor for details.

⁴ Seagate does not recommend operating at sustained extreme temperatures. Operating at higher temperatures will reduce useful life of the product.

AMERICAS	Seagate Technology LLC 10200 South De Anza Boulevard, Cupertino, California 95014, United States, 408-658-1000
ASIA/PACIFIC	Seagate Singapore International Headquarters Pte. Ltd. 7000 Ang Mo Kio Avenue 5, Singapore 569877, 65-6485-3888
EUROPE, MIDDLE EAST, AND AFRICA	Seagate Technology SAS 16-18, rue du Dôme, 92100 Boulogne-Billancourt, France, 33 1-4186 10 00

© 2019 Seagate Technology LLC. All rights reserved. Seagate, Seagate Technology and the Spiral logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. ImagePerfect, SkyHawk and the SkyHawk AI logo are either trademarks or registered trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Actual data rates may vary depending on operating environment and other factors, such as chosen interface and disk capacity. Seagate reserves the right to change, without notice, product offerings or specifications. DS1960.5-1903US March 2019