

# Desktop SSHD

## Data Sheet

### Performance. Capacity. Affordable Price.

- The first solid state hybrid drive (SSHD) in a 3.5-inch form factor
- Boots and performs like an SSD<sup>1</sup>
- SATA 6Gb/s with NCQ for interface speed
- Faster than a traditional HDD<sup>1</sup>
- All-in-one design for simplicity and ease of installation
- Installs and operates like a standard hard drive: cross-platform, no drivers or additional software required
- Massive 1TB, 2TB and 4TB capacities combined with SSD-like performance<sup>1</sup>
- Backed by a 3-year limited warranty

### Best-Fit Applications

- Desktop PCs
- Workstations
- High-performance direct-attached storage (DAS) devices

<sup>1</sup> Performance may vary depending on user's hardware configuration and operating system.



# Desktop SSHD



Specifications	4TB <sup>1</sup>	2TB <sup>1</sup>	1TB <sup>1</sup>
Model Number	ST4000DX001	ST2000DX001	ST1000DX001
Interface	SATA 6Gb/s NCQ	SATA 6Gb/s NCQ	SATA 6Gb/s NCQ
<b>Performance</b>			
NAND Type/Size	MLC/8GB	MLC/8GB	MLC/8GB
DRAM Cache (MB)	64	64	64
SATA Transfer Rates Supported (Gb/s)	6.0/3.0/1.5	6.0/3.0/1.5	6.0/3.0/1.5
Seek Average, Read (ms)	<12	<9.5	<8.5
Seek Average, Write (ms)	<12	<9.5	<8.5
Average Data Rate, Read, Avg All Zones (MB/s)	146	156	156
Average Data Rate From NAND Media (MB/s)	190	190	190
Max Sustained Data Rate, OD Read (MB/s)	180	210	210
<b>Configuration/Organization</b>			
Heads/Disks	8/4	4/2	2/1
Bytes per Sector	4096	4096	4096
<b>Reliability/Data Integrity</b>			
Load/Unload Cycles	300,000	300,000	300,000
Nonrecoverable Read Errors per Bits Read, Max	1 per 10E14	1 per 10E14	1 per 10E14
Predicted Annualized Failure Rate (AFR)	<1%	<1%	<1%
<b>Power Management</b>			
Power (W)			
Operating, Typical	7.5	6.7	5.9
Idle2, Typical	—	4.5	3.36
Idle, Typical	6.2	—	—
Standby Mode	0.75	0.75	0.63
Sleep Mode	0.75	0.75	0.63
<b>Environmental</b>			
Temperature (°C)			
Operating	0 to 60	0 to 60	0 to 60
Nonoperating	-40 to 70	-40 to 70	-40 to 70
<b>Physical</b>			
Height (in/mm)	1.028/26.11	1.028/26.11	0.782/19.87
Width (in/mm)	4.0/101.6	4.0/101.6	4.0/101.6
Depth (in/mm)	5.787/146.99	5.787/146.99	5.787/146.99
Weight (lb/g)	1.345/610	1.18/535	0.88/400
Carton Unit Quantity	20	20	25
Cartons per Pallet	40	40	40
Cartons per Layer	8	8	8

<sup>1</sup> One gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one trillion bytes when referring to drive capacity.

[www.seagate.com](http://www.seagate.com)

AMERICAS  
ASIA/PACIFIC  
EUROPE, MIDDLE EAST AND AFRICA

Seagate Technology LLC 10200 South De Anza Boulevard, Cupertino, California 95014, United States, 408-658-1000  
Seagate Singapore International Headquarters Pte. Ltd. 7000 Ang Mo Kio Avenue 5, Singapore 569877, 65-6485-3888  
Seagate Technology SAS 16-18, rue du Dôme, 92100 Boulogne-Billancourt, France, 33 1-4186 10 00

© 2013 Seagate Technology LLC. All rights reserved. Printed in USA. Seagate, Seagate Technology and the Wave logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Actual data rates may vary depending on operating environment and other factors. Seagate reserves the right to change, without notice, product offerings or specifications. DS1788.2-1308US, August 2013