

# Enterprise Capacity 2.5 HDD

## Data Sheet

### Design Small and Deliver BIG - 2.5-Inch Nearline Drive

- Up to 2 TB capacity in 15mm z-height, 2.5-inch form factor for space-constrained data centres
- Designed for high-density storage solutions requiring environmentally sound low power consumption and low weight for maximum storage efficiency
- Choose 12 Gb/s SAS for high data integrity, scalability and fast data access or SATA 6 Gb/s for economical nearline performance
- Third-generation, enterprise-class reliability for 24x7 environmental robustness
- Advanced sector formats (4K Native and 512 Emulation) as well as 512 Native support for legacy systems
- Highest efficiency with over 50% improvement in watts/TB, and 18% sequential performance improvement compared to the previous generation
- Improved rotational vibration tolerance and head micro-actuation maximises system availability and performance
- Lowest enterprise operating power and enhanced PowerChoice™ options for additional power savings during idle periods
- Protect data where it lives - on the drive - by choosing from government-grade SED FIPS 140-2 option or SED models with Seagate Instant Secure Erase technology for easy and cost-effective drive disposal<sup>1</sup>

### Best-fit Applications

- Storage-hungry business applications
- Storage area networks (SAN) and network attached storage (NAS)
- Maximum-capacity entry-level servers and blade servers
- Rich media content storage
- Enterprise backup and restore - D2D, virtual tape
- Cloud computing



<sup>1</sup> Self-Encrypting Drives (SED) and FIPS 140-2 Validated drives are not available in all models or countries. May require TCG-compliant host or controller support. Instant Secure Erase (ISE) functionality meets the ISO/IEC 27040 and NIST 800-88 guidelines for complete and authoritative drive sanitization.



# Enterprise Capacity 2.5 HDD



Specifications	12 Gb/s SAS					
	4K Native		5xx Emulation		5xx Native	
	2 TB <sup>1</sup>	1 TB <sup>1</sup>	2 TB <sup>1</sup>	1 TB <sup>1</sup>	2 TB <sup>1</sup>	1 TB <sup>1</sup>
Standard Model Number	ST2000NX0263	ST1000NX0323	ST2000NX0273	ST1000NX0333	ST2000NX0433	ST1000NX0453
SED Model Number	ST2000NX0323 <sup>2</sup>	ST1000NX0363 <sup>2</sup>	ST2000NX0343 <sup>2</sup>	ST1000NX0373 <sup>2</sup>	—	—
SED-FIPS Model Number	ST2000NX0333 <sup>2</sup>	—	ST2000NX0353 <sup>2</sup>	—	—	—
<b>Features</b>						
PowerChoice™ On-Demand Power Option	Yes	Yes	Yes	Yes	Yes	Yes
Protection Information	Yes	Yes	Yes	Yes	Yes	Yes
Low Halogen	Yes	Yes	Yes	Yes	Yes	Yes
RAID Rebuild™	Yes	Yes	Yes	Yes	Yes	Yes
<b>Reliability/Data Integrity</b>						
Mean Time Between Failures (MTBF, hours)	2.0 million	2.0 million	2.0 million	2.0 million	2.0 million	2.0 million
Reliability Rating @ Full 24x7 operation (AFR)	0.44%	0.44%	0.44%	0.44%	0.44%	0.44%
Non-recoverable Read Errors per Bits Read	1 sector per 10 <sup>15</sup>	1 sector per 10 <sup>15</sup>	1 sector per 10 <sup>15</sup>	1 sector per 10 <sup>15</sup>	1 sector per 10 <sup>15</sup>	1 sector per 10 <sup>15</sup>
Power-On Hours per Year	8,760	8,760	8,760	8,760	8,760	8,760
Bytes per Sector	4K	4K	512, 520, 528	512, 520, 528	512, 520, 528	512, 520, 528
Limited Warranty (years)	5	5	5	5	5	5
<b>Performance</b>						
Spindle Speed (RPM)	7,200	7,200	7,200	7,200	7,200	7,200
Cache Buffer, Multisegmented (MB)	128	128	128	128	128	128
Interface Access Speed (Gb/s)	12.0, 6.0, 3.0	12.0, 6.0, 3.0	12.0, 6.0, 3.0	12.0, 6.0, 3.0	12.0, 6.0, 3.0	12.0, 6.0, 3.0
Max. Sustained Transfer Rate (MB/s)	136	136	136	136	136	136
Average Latency (ms)	4.16	4.16	4.16	4.16	4.16	4.16
Interface Ports	Dual	Dual	Dual	Dual	Dual	Dual
RV Tolerance (rad/s <sup>2</sup> to 1,800 Hz)	16	16	16	16	16	16
<b>Power Management</b>						
Idling Power (W)	3.53	3.29	3.53	3.29	3.53	3.29
Typical Operating, Random Read (W)	6.02	5.9	6.02	5.9	6.02	5.9
PowerChoice™ Technology (Standby) (W)	1.52	1.52	1.52	1.52	1.52	1.52
Power Supply Requirements	+12 V and +5 V	+12 V and +5 V	+12 V and +5 V	+12 V and +5 V	+12 V and +5 V	+12 V and +5 V
<b>Environmental</b>						
Temperature, Operating (°C)	5 to 55	5 to 55	5 to 55	5 to 55	5 to 55	5 to 55
Vibration, Operating, 5 Hz to 500 Hz (Gs)	0.5	0.5	0.5	0.5	0.5	0.5
Vibration, Non-operating, 5 Hz to 500 Hz (Gs)	3.0	3.0	3.0	3.0	3.0	3.0
Shock, Operating, 2ms (Gs)	25	25	25	25	25	25
Shock, Non-operating, 2 ms (Gs)	400	400	400	400	400	400
Acoustics, typical - idling (bels)	2.8	2.8	2.8	2.8	2.8	2.8
Acoustics, typical - seek (bels)	3.2	3.2	3.2	3.2	3.2	3.2
<b>Physical</b>						
Height (in/mm) <sup>3</sup>	0.591/15.00	0.591/15.00	0.591/15.00	0.591/15.00	0.591/15.00	0.591/15.00
Width (in/mm) <sup>3</sup>	2.760/70.10	2.760/70.10	2.760/70.10	2.760/70.10	2.760/70.10	2.760/70.10
Depth (in/mm) <sup>3</sup>	3.955/100.45	3.955/100.45	3.955/100.45	3.955/100.45	3.955/100.45	3.955/100.45
Weight (lb/kg)	0.437/0.198	0.419/0.190	0.437/0.198	0.419/0.190	0.437/0.198	0.437/0.198
Carton Unit Quantity	40	40	40	40	40	40
Cartons per Pallet	60	60	60	60	60	60
Cartons per Layer	10	10	10	10	10	10

<sup>1</sup> One gigabyte, or GB equals one billion bytes; and one terabyte or TB, equals one trillion bytes when referring to drive capacity.

<sup>2</sup> Self-Encrypting Drives (SED) and FIPS 140-2 Validated drives are not available in all models or countries. May require TCG-compliant host or controller support. Instant Secure Erase (ISE) functionality meets the ISO/IEC 27040 and NIST 800-88 guidelines for complete and authoritative drive sanitization.

<sup>3</sup> These base deck dimensions conform to the Small Form Factor Standard (SFF-8201) found at [www.sffcommittee.org](http://www.sffcommittee.org). For connector-related dimensions, see SFF-8223.





# Enterprise Capacity 2.5 HDD



Specifications	6 Gb/s SATA					
	4K Native		512 Emulation		512 Native	
	2 TB <sup>1</sup>	1 TB <sup>1</sup>	2 TB <sup>1</sup>	1 TB <sup>1</sup>	2 TB <sup>1</sup>	1 TB <sup>1</sup>
Standard Model Number	ST2000NX0243	ST1000NX0303	ST2000NX0253	ST1000NX0313	ST2000NX0403	ST1000NX0423
SED Model Number	ST2000NX0283 <sup>2</sup>	ST1000NX0343 <sup>2</sup>	ST2000NX0303 <sup>2</sup>	ST1000NX0353 <sup>2</sup>	—	—
Features						
PowerChoice™ On-Demand Power Option	Yes	Yes	Yes	Yes	Yes	Yes
Low Halogen	Yes	Yes	Yes	Yes	Yes	Yes
RAID Rebuild™	Yes	Yes	Yes	Yes	Yes	Yes
Reliability/Data Integrity						
Mean Time Between Failures (MTBF, hours)	2.0 million	2.0 million	2.0 million	2.0 million	2.0 million	2.0 million
Reliability Rating @ Full 24x7 operation (AFR)	0.44%	0.44%	0.44%	0.44%	0.44%	0.44%
Non-recoverable Read Errors per Bits Read	1 sector per 10 <sup>15</sup>	1 sector per 10 <sup>15</sup>	1 sector per 10 <sup>15</sup>	1 sector per 10 <sup>15</sup>	1 sector per 10 <sup>15</sup>	1 sector per 10 <sup>15</sup>
Power-On Hours per Year	8,760	8,760	8,760	8,760	8,760	8,760
Bytes per Sector	4K	4K	512	512	512	512
Limited Warranty (years)	5	5	5	5	5	5
Performance						
Spindle Speed (RPM)	7,200	7,200	7,200	7,200	7,200	7,200
Cache Buffer, Multisegmented (MB)	128	128	128	128	128	128
Interface Access Speed (Gb/s)	6.0, 3.0, 1.5	6.0, 3.0, 1.5	6.0, 3.0, 1.5	6.0, 3.0, 1.5	6.0, 3.0, 1.5	6.0, 3.0, 1.5
Max. Sustained Transfer Rate (MB/s)	136	136	136	136	136	136
Average Latency (ms)	4.16	4.16	4.16	4.16	4.16	4.16
Interface Ports	Single	Single	Single	Single	Single	Single
RV Tolerance (rad/s <sup>2</sup> to 1,800 Hz)	16	16	16	16	16	16
Power Management						
Idling Power (W)	3.87	3.51	3.87	3.51	3.87	3.51
Typical Operating, Random Read (W)	5.22	4.74	5.22	4.74	5.22	4.74
PowerChoice™ Technology (Standby) (W)	1.14	1.14	1.14	1.14	1.14	1.14
Power Supply Requirements	+12 V and +5 V	+12 V and +5 V	+12 V and +5 V	+12 V and +5 V	+12 V and +5 V	+12 V and +5 V
Environmental						
Temperature, Operating (°C)	5 to 55	5 to 55	5 to 55	5 to 55	5 to 55	5 to 55
Vibration, Operating, 5 Hz to 500 Hz (Gs)	0.5	0.5	0.5	0.5	0.5	0.5
Vibration, Non-operating, 5 Hz to 500 Hz (Gs)	3.0	3.0	3.0	3.0	3.0	3.0
Shock, Operating, 2ms (Gs)	25	25	25	25	25	25
Shock, Non-operating, 2 ms (Gs)	400	400	400	400	400	400
Acoustics, typical - idling (bels)	2.8	2.8	2.8	2.8	2.8	2.8
Acoustics, typical - seek (bels)	3.2	3.2	3.2	3.2	3.2	3.2
Physical						
Height (in/mm) <sup>3</sup>	0.591/15.00	0.591/15.00	0.591/15.00	0.591/15.00	0.591/15.00	0.591/15.00
Width (in/mm) <sup>3</sup>	2.760/70.10	2.760/70.10	2.760/70.10	2.760/70.10	2.760/70.10	2.760/70.10
Depth (in/mm) <sup>3</sup>	3.955/100.45	3.955/100.45	3.955/100.45	3.955/100.45	3.955/100.45	3.955/100.45
Weight (lb/kg)	0.437/0.198	0.419/0.190	0.437/0.198	0.419/0.190	0.437/0.198	0.419/0.190
Carton Unit Quantity	40	40	40	40	40	40
Cartons per Pallet	60	60	60	60	60	60
Cartons per Layer	10	10	10	10	10	10

<sup>1</sup> One gigabyte, or GB equals one billion bytes; and one terabyte or TB, equals one trillion bytes when referring to drive capacity.

<sup>2</sup> Self-Encrypting Drives (SED) and FIPS 140-2 Validated drives are not available in all models or countries. May require TCG-compliant host or controller support. Instant Secure Erase (ISE) functionality meets the ISO/IEC 27040 and NIST 800-88 guidelines for complete and authoritative drive sanitization.

<sup>3</sup> These base deck dimensions conform to the Small Form Factor Standard (SFF-8201) found at [www.sffcommittee.org](http://www.sffcommittee.org). For connector-related dimensions, see SFF-8223.



[seagate.com](http://seagate.com)

AMERICAS Seagate Technology LLC 10200 South De Anza Boulevard, Cupertino, California 95014, United States, +1 408 658 1000  
 ASIA/PACIFIC Seagate Singapore International Headquarters Pte. Ltd. 7000 Ang Mo Kio Avenue 5, Singapore 569877, +65 6485 3888  
 EUROPE, MIDDLE EAST AND AFRICA Seagate Technology SAS 16-18 rue du Dôme, 92100 Boulogne-Billancourt, France, +33 1 41 86 10 00

© 2016 Seagate Technology LLC. All rights reserved. Printed in USA. Seagate, Seagate Technology and the Spiral logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. PowerChoice and RAID Rebuild are either trademarks or registered trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes; and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Actual data rates may vary depending on operating environment and other factors. The export or re-export of Seagate hardware or software is regulated by the U.S. Department of Commerce, Bureau of Industry and Security (for more information, visit [www.bis.doc.gov](http://www.bis.doc.gov)), and may be controlled for export, import and use in other countries. Seagate reserves the right to change, without notice, product offerings or specifications. DS1719.8-1602GB, February 2016