

Enterprise Performance 15K HDD

Data Sheet

High-Performing, Up to 600GB, Small Form Factor 15K Hard Drive

- Stores twice the amount of Tier 1 data over previous generation, without increasing drive count, in 2.5-inch form factor
- Enables faster transaction processing, which can result in increased revenue generation and improved customer satisfaction
- Latest 12Gb/s SAS interface for improved scalability
- Industry's highest MTBF at 2.0M hours
- Support for all drive formats, including 512 Native, 512 Emulation and 4K Native
- Provides up to 18% improvement in SDR performance over prior generation¹
- SAS-based Protection Information (PI) helps protect against inadvertent data change.²
- Self-Encrypting Drive (SED) option (AES-256) helps cut IT drive retirement costs while helping securely protect data where it lives—on the drive.³
- SED models can be used as standard drives, as ISE feature for easy drive disposal or as part of a more secure solution.³
- FIPS Self-Encrypting Drive option helps protect *Sensitive but Unclassified* and *Protected* class data.^{3,4}

Best-Fit Applications

- High-performance Tier 1 enterprise servers
- Blade, rack and tower servers hosting transaction-based applications
- Power- and space-constrained data centers
- Compliance and data security initiatives

¹ Actual improvement varies depending on queue depth and transfer size.

² Protection Information (PI) feature requires PI-compliant host or controller support.

³ Self-Encrypting Drives (SED) and FIPS SEDs are not available in all models or countries. May require TCG-compliant host or controller support.

⁴ FIPS in review. See FIPS 140-2 Level 2 Certificate at <http://csrc.nist.gov/groups/STM/cmvp/documents/140-1/1401vend.htm>



Enterprise Performance 15K HDD



Specifications	512 Native ⁴			512 Emulation			4K Native		
	600GB ¹	450GB ¹	300GB ¹	600GB ¹	450GB ¹	300GB ¹	600GB ¹	450GB ¹	300GB ¹
Standard Model	ST600MP0005	ST450MP0005	ST300MP0005	ST600MP0035	ST450MP0035	ST300MP0035	ST600MP0065	ST450MP0065	ST300MP0065
SED Model	ST600MP0015 ²	ST450MP0015 ²	ST300MP0015 ²	ST600MP0045 ²	ST450MP0045 ²	ST300MP0045 ²	ST600MP0075 ²	ST450MP0075 ²	ST300MP0075 ²
SED FIPS 140-2 Model	ST600MP0025 ^{2,3}	—	—	ST600MP0055 ^{2,3}	—	—	ST600MP0085 ^{2,3}	—	—
Interface	12Gb/s SAS	12Gb/s SAS	12Gb/s SAS	12Gb/s SAS	12Gb/s SAS	12Gb/s SAS	12Gb/s SAS	12Gb/s SAS	12Gb/s SAS
Performance									
Average Latency (ms)	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0
Sustained Transfer Rate (Outer to Inner Diameter) MiB/s	233 to 160	233 to 160	233 to 160	246 to 180	246 to 180	246 to 180	246 to 180	246 to 180	246 to 180
Max. Instantaneous Transfer Rate (SAS dual port) MB/s	2400	2400	2400	2400	2400	2400	2400	2400	2400
Cache, Multisegmented (MB)	128	128	128	128	128	128	128	128	128
Seagate Turbo-Boost Option									
NAND Flash Type	eMLC	eMLC	eMLC	eMLC	eMLC	eMLC	eMLC	eMLC	eMLC
NAND Flash Size (GB)	32	32	32	32	32	32	32	32	32
Configuration/Reliability									
Disks/Heads	3/6	3/6	2/4	3/6	3/6	2/4	3/6	3/6	2/4
Nonrecoverable Read Errors per Bits Read, Max	1 per 10E16	1 per 10E16	1 per 10E16	1 per 10E16	1 per 10E16	1 per 10E16	1 per 10E16	1 per 10E16	1 per 10E16
Annualized Failure Rate (AFR)	0.44%	0.44%	0.44%	0.44%	0.44%	0.44%	0.44%	0.44%	0.44%
Limited Usage-Based Warranty (years) ⁵	5	5	5	5	5	5	5	5	5
Power Management									
Typical Op (A) +5V/+12V	0.44/0.54	0.41/0.52	0.46/0.51	0.44/0.54	0.41/0.52	0.46/0.51	0.44/0.54	0.41/0.52	0.46/0.51
Average Idle Power (W)	5.3	5.2	4.8	5.3	5.2	4.8	5.3	5.2	4.8
Average Operating Power (W)	8.7	8.4	8.4	8.7	8.4	8.4	8.7	8.4	8.4
Environmental									
Ambient Temperature, Operating (C°)	5 to 55	5 to 55	5 to 55	5 to 55	5 to 55	5 to 55	5 to 55	5 to 55	5 to 55
Ambient Temperature, Nonoperating (C°)	-40 to 70	-40 to 70	-40 to 70	-40 to 70	-40 to 70	-40 to 70	-40 to 70	-40 to 70	-40 to 70
Temperature Change Rate/Hr, Max (°C)	20	20	20	20	20	20	20	20	20
Relative Humidity, Noncondensing (max gradient 20%/hour)	5% to 95%	5% to 95%	5% to 95%	5% to 95%	5% to 95%	5% to 95%	5% to 95%	5% to 95%	5% to 95%
Shock, Max Operating: 11ms (Gs)	40	40	40	40	40	40	40	40	40
Shock, Max Nonoperating: 2ms (Gs)	400	400	400	400	400	400	400	400	400
Vibration, Operating: <400Hz (Gs)	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5
Vibration, Nonoperating: <500Hz (Gs)	2.4	2.4	2.4	2.4	2.4	2.4	2.4	2.4	2.4
Physical									
Height (in/mm, max) ⁶	0.591/15.00	0.591/15.00	0.591/15.00	0.591/15.00	0.591/15.00	0.591/15.00	0.591/15.00	0.591/15.00	0.591/15.00
Width (in/mm, max) ⁶	2.750/69.85	2.750/69.85	2.750/69.85	2.750/69.85	2.750/69.85	2.750/69.85	2.750/69.85	2.750/69.85	2.750/69.85
Depth (in/mm, max) ⁶	3.955/100.45	3.955/100.45	3.955/100.45	3.955/100.45	3.955/100.45	3.955/100.45	3.955/100.45	3.955/100.45	3.955/100.45
Weight (lb/kg)	0.507/0.230	0.507/0.230	0.496/0.225	0.507/0.230	0.507/0.230	0.496/0.225	0.507/0.230	0.507/0.230	0.496/0.225
Carton Unit Quantity	30	30	30	30	30	30	30	30	30
Cartons per Pallet	50	50	50	50	50	50	50	50	50
Cartons per Layer	10	10	10	10	10	10	10	10	10

1 One gigabyte, or GB, equals one billion bytes when referring to drive capacity.

2 Self-Encrypting Drives (SED) and FIPS 140-2 Validated drives are not available in all models or countries. May require TCG-Compliant host or controller support.

3 FIPS 140-2 in review. See FIPS 140-2 Level 2 Certificate at <http://csrc.nist.gov/groups/STM/cmvp/validation.html>

4 512 Emulation and 4K Native models will provide a higher level of performance in 4K-aligned systems.

5 Warranty period is either 5 years or when the device reaches the Total TBW Over Warranty Period, whichever comes first.

6 The drive physical dimensions conform to the Small Form Factor Standard (SFF-8201) found at www.sffcommittee.org. For connector-related dimensions, see SFF-8223.



www.seagate.com

AMERICAS
ASIA/PACIFIC
EUROPE, MIDDLE EAST AND AFRICA

Seagate Technology LLC 10200 South De Anza Boulevard, Cupertino, California 95014, United States, 408-658-1000
Seagate Singapore International Headquarters Pte. Ltd. 7000 Ang Mo Kio Avenue 5, Singapore 569877, 65-6485-3888
Seagate Technology SAS 16-18, rue du Dôme, 92100 Boulogne-Billancourt, France, 33 1-4186 10 00