

NAS HDD

HARD DISK DRIVE KIT Data Sheet

Best-Performing, Highest-Capacity Storage for 1- to 8-Bay NAS Systems

- Seagate® NAS HDD kits are built and tested to provide industry-leading performance for small NAS systems.
- NASWorks™ technology supports customized error recovery controls, power management and vibration tolerance for optimal performance and reliability in a 1- to 8-bay solution with 20 users or less.
- NAS error recovery controls optimize drive health by helping to ensure drives are not dropped from the NAS and sent into a RAID rebuild.
- Improved vibration tolerance and emission in multi-drive systems with dual-plane balance.
- Advanced power management supports multiple power profiles for low-power, 24x7 performance.
- Quiet drive operation enhances customer experience in living room or office environments.

Best-Fit Applications

- Home/SOHO NAS desktop towers
- Desktop RAID
- Backup and disaster recovery
- Print and file servers
- Multimedia server/storage
- Archival
- Virtualization
- Small-business file sharing
- Backup servers





NAS HDD

HARD DISK DRIVE KIT



Specifications				
Retail Packaging	Product Dimensions	Box Dimensions	Master Carton Dimensions	Pallet Dimensions
Height (in/mm)	5.75/146.05	5.94/150.83	15.75/400.05	47.94/1217.68
Width (in/mm)	4.0/101.6	7.75/196.85	5.0/127.0	37.44/950.97
Depth (in/mm)	1.0/25.4	2.38/60.325	6.06/154.0	45.13/1146.3
Weight (lb/kg)	1.39/0.63	1.74/0.78	7.38/3.35	1030.60/468.46
Quantities				
Boxes per Master Carton	4			
Master Cartons per Pallet	126			
Pallet Layers	6			
NASWorks				
Number of Drive Bays Supported	1 to 8			
Dual-Plane Balance	Yes			
Vibration Tolerance for Small NAS	Yes			
NASWorks Error Recovery Control	Yes			
Voltage (Per Drive)				
Voltage Tolerance, Including Noise (5V)	±5%			
Voltage Tolerance, Including Noise (12V)	±10%			
Power Management (Per Drive)				
Startup Current, Average (12V, A)	2			
Operating Mode (W)	4.8			
Idle Average (W)	3.95			
Standby/Sleep Mode (W)	0.5			
Power Management				
Startup Current (12V, A max)	2			
Operating Average (W)	4.8			
Idle Average (W)	3.95			
Standby/Sleep Mode (typical, W)	0.5			
Environmental (Per Drive)				
Temperature (°C)				
Operating (ambient min)	0			
Operating (drive case max)	70			
Nonoperating (ambient)	−40 to 70			
Temperature Gradient, Operating/Nonoperating (°C per hour max)	20/30			
Shock				
Operating: 2ms (max, Gs)	80			
Nonoperating: 2ms (max, Gs)	300			
Acoustics				
Idle (typical, bels) ¹	2.3			
Operational (typical, bels)	2.5			
Reliability (Per Drive)				
Load/Unload ²	600,000			
Nonrecoverable Read Errors per Bits Read, Max	1 per 10E14			
Power-On Hours	8760			
Mean Time Between Failures (MTBF, hours)	1M			
Warranty, Limited (years)	3			
System Requirements				
SATA 6Gb/s interface connector or motherboard or add-in card (backward compatible to SATA 3Gb/s)				
Works with all current versions of Windows®, Mac® and Linux				
See NAS Manufacturers web pages for more information on compatibility				
Inside the Box				
Seagate® NAS HDD				
Quick installation guide				
3-year limited warranty				

Region	Product	Capacity ³	Model Number	UPC Code	EAN	Multipack UPC
WW	NAS HDD	4TB	STBD4000100	763649073117	7636490071669	10763649073114

¹ Idle measured in Idle1 state.

² Load/Unload tested to 600,000 cycles.

³ One terabyte, or TB, equals one trillion bytes when referring to drive capacity.

seagate.com

AMERICAS Seagate Technology LLC 10200 South De Anza Boulevard, Cupertino, California 95014, United States, 408-658-1000
ASIA/PACIFIC Seagate Singapore International Headquarters Pte. Ltd. 7000 Ang Mo Kio Avenue 5, Singapore 569877, 65-6485-3888
EUROPE, MIDDLE EAST AND AFRICA Seagate Technology SAS 16-18, rue du Dôme, 92100 Boulogne-Billancourt, France, 33 1-4186 10 00

© 2015 Seagate Technology LLC. All rights reserved. Printed in USA. Seagate, Seagate Technology and the Spiral logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. NASWorks is either a trademark or registered trademark of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Actual data rates may vary depending on operating environment and other factors. Seagate reserves the right to change, without notice, product offerings or specifications. DS1856.1-1506WW, June 2015